

ChevronTexaco HDAX® 50/50 Coolant

Category: Fluid

Material Notes:

FeaturesChevron HDAX 50/50 Coolant is a mixture of ethylene glycol, deionized water and a highly effective, heavyduty corrosion inhibitor package. Chevron HDAX 50/50 Coolant as purchased givesfreeze protection down to minus -37°C (-34°F) and boil over protection to 129°C (265°F) with a 15 lb. pressure cap. This product needs no pre-charging with supplemental coolant additives (SCAs). Chevron HDAX 50/50 Coolant is compatible with other traditional and pre-charged, low silicate antifreezes Applications Chevron HDAX 50/50 Coolant is specifically blended for use in stationary engines using various fuel sources and for on-road and off-road heavy duty diesels. This product meets the requirements of TMC RP329 and ASTM D 6210 for heavy-duty diesel service. Note: This product is not to be used to protect the inside of potable water systems against freezing.

Order this product through the following link:

http://www.lookpolymers.com/polymer_ChevronTexaco-HDAX-5050-Coolant.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.13 g/cc	1.13 g/cc	
рН	10.5	10.5	1:2 dilution with water; ASTM D1287

Thermal Properties	Metric	English	Comments
Melting Point	-34.0 °C	-29.2 °F	

Descriptive Properties	Value	Comments	
Color	Purple/Clear with no debris		
Reserve Alkalinity ASTM D1121	6		
Silicate, %	0.09		

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China