

ChevronTexaco HDAX® SAE 30 Low Ash Gas Engine Oil

Category : Fluid , Lubricant

Material Notes:

Features Chevron HDAX Low Ash Gas Engine Oils are high quality, bright stock-free, low ash, dispersant/detergent type engine oils. They are formulated with ISOSYN™ base stocks and an additive package containing ashless dispersant, oxidation inhibitors, metallic detergents, and a metallic antiwear agent. Chevron HDAX Low Ash Gas Engine Oils provide outstanding oxidation and nitration resistance, which reduce the buildup of insolubles and provide extended oil and filter life. Chevron HDAX Low Ash Gas Engine Oils give excellent protection against ring and liner scuffing and wear. They also minimize valve recession in four-stroke engines and provide excellent piston and ring belt deposit control and effectively protect against the formation and buildup of engine sludge.

Applications Chevron HDAX Low Ash Gas Engine Oils are especially formulated to meet API CD performance and Engelhard's NSCR catalyst compatibility requirements. Chevron HDAX Low Ash Gas Engine Oils are recommended for four-cycle and selected two-cycle stationary engines fueled by natural or synthetic gas and gas from digester and landfill sources. These oils are recommended for four-cycle engines manufactured by Caterpillar, Delaval-Enterprise, Dresser-Rand Categories I, II and III (SAE 30), Fairbanks-Morse/MEP, Superior, Waukesha, and Worthington. They are also satisfactory for selected two-cycle engines manufactured by Clark-Dresser and Worthington.

Order this product through the following link:

http://www.lookpolymers.com/polymer_ChevronTexaco-HDAX-SAE-30-Low-Ash-Gas-Engine-Oil.php

| Physical Properties | Metric | English | Comments |
|--------------------------------------|----------|----------|-----------------------------|
| API Gravity | 29.8 ° | 29.8 ° | |
| Viscosity Measurement | 104 | 104 | Viscosity Index; ASTM D2270 |
| Kinematic Viscosity at 40°C (104°F) | 97.3 cSt | 97.3 cSt | ASTM D445 |
| Kinematic Viscosity at 100°C (212°F) | 11.4 cSt | 11.4 cSt | ASTM D445 |
| Ash | 0.50 % | 0.50 % | Sulfated Ash wt% |

| Thermal Properties | Metric | English | Comments |
|--------------------|----------|----------|----------|
| Pour Point | -24.0 °C | -11.2 °F | ASTM D97 |
| Flash Point | 222 °C | 432 °F | ASTM D92 |

| Component Elements Properties | Metric | English | Comments |
|-------------------------------|---------|---------|----------|
| Phosphorous, P | 0.027 % | 0.027 % | |
| Zinc, Zn | 0.032 % | 0.032 % | |

| Chemical Properties | Metric | English | Comments |
|---------------------|--------|---------|------------|
| Total Base Number | 4.2 | 4.2 | ASTM D2896 |

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China