

ChevronTexaco HPLX SAE 40 Chevron HPLX Low Ash Gas Engine Oil

Category : Fluid , Lubricant

Material Notes:

Features Chevron HPLX Low Ash Gas Engine Oils are high quality, bright stock-free, low ash, dispersant/detergent type engine oils. They are formulated with ISOSYN™ base stocks and an additive package containing ashless dispersant, oxidation inhibitors, metallic detergents, and a metallic antiwear agent. Chevron HPLX Low Ash Gas Engine Oils provide excellent oxidation and nitration resistance, which reduce the buildup of insolubles and provide extended oil and filter life. Chevron HPLX Low Ash Gas Engine Oils also give excellent protection against ring and liner scuffing and wear. They also minimize valve recession in four-stroke engines and provide excellent piston and ring belt deposit control and effectively protect against the formation and buildup of engine sludge.

Applications Chevron HPLX Low Ash Gas Engine Oils are recommended for four-stroke and selected two-stroke stationary engines fueled by natural or synthetic gas and gas from digester and landfill sources. Recommended for four-stroke engines manufactured by: Caterpillar, Delaval, Enterprise, Dresser-Rand. Categories I, II, and III (SAE 30) Superior, Waukesha, Worthington. Satisfactory for selected two-stroke engines manufactured by: Ajax, Clark-Dresser, Fairbanks-Morse, MEP, Worthington.

Chevron HPLX Low Ash Gas Engine Oils are formulated to meet NSCR catalyst compatibility requirements and are especially suited for installations requiring low phosphorus oil to prevent exhaust catalyst poisoning. Chevron HPLX Low Ash Gas Engine Oils are suitable for use with fuels containing low levels of sulfur and Chloro-Fluoro-Carbons (CFC). In sour gas/high CFC applications, an oil with higher base reserve may be required. Chevron HPLX Low Ash Gas Engine Oils SAE 30 and 40 are formulated to meet the performance requirements of API Service Category CD1/CF.

Order this product through the following link:

http://www.lookpolymers.com/polymer_ChevronTexaco-HPLX-SAE-40-Chevron-HPLX-Low-Ash-Gas-Engine-Oil.php

Physical Properties	Metric	English	Comments
API Gravity	29.4 °	29.4 °	
Viscosity Measurement	104	104	Viscosity Index; ASTM D2270
Kinematic Viscosity at 40°C (104°F)	124 cSt	124 cSt	ASTM D445
Kinematic Viscosity at 100°C (212°F)	13.5 cSt	13.5 cSt	ASTM D445
Ash	0.48 %	0.48 %	Sulfated Ash wt%

Thermal Properties	Metric	English	Comments
Pour Point	-18.0 °C	-0.400 °F	ASTM D97
Flash Point	230 °C	446 °F	ASTM D92

Component Elements Properties	Metric	English	Comments
Phosphorous, P	0.028 %	0.028 %	
Zinc, Zn	0.030 %	0.030 %	

Chemical Properties	Metric	English	Comments
Total Base Number	5.1	5.1	ASTM D2896

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com
Email : sales@lookpolymers.com
Tel : +86 021-51131842
Mobile : +86 13061808058
Skype : lookpolymers
Address : United North Road 215,Fengxian District, Shanghai City,China