

## ChevronTexaco Havoline® ATF+3® Automatic Transmission Fluid

Category : Fluid , Lubricant

### Material Notes:

Havoline Automatic Transmission Fluid ATF+3 delivers value through: Correct viscosity and frictional characteristics to ensure smooth operation in Chrysler transmissions. Long-lasting viscosity modifiers for longer fluid life. Havoline Automatic Transmission Fluid ATF+3 is designed specifically for use in Chrysler® automatic transmissions and automatic transaxles where a Mopar ATF PLUS®, ATF+2® or ATF+3® fluid is specified. Havoline Automatic Transmission Fluid ATF+3 is designed to maintain its viscosity through excellent oxidation stability and use of long lasting viscosity modifiers. It has improved low temperature fluidity and viscosity breakdown performance over previous generation Chrysler ATF fluids. Havoline Automatic Transmission Fluid ATF+3 is specially formulated to give full protection in all critical areas of Chrysler transmission operation. Havoline Automatic Transmission Fluid ATF+3: Lubricates and prevents wear in gears, clutches, and bearings. Transfers engine power effectively. Serves as a hydraulic fluid for the shift control system. Removes heat efficiently. Operates well over a wide temperature range. Resists thermal and oxidative breakdown. Provides sufficient viscosity at high temperatures with minimal shear down. Gives proper friction performance for Chrysler vehicles (smooth shift feel, no shudder). Protects seals, gaskets, and other nonferrous components. Prevents sludge and varnish formation. Resists foaming. Havoline Automatic Transmission Fluid ATF+3 is designed for use in all Chrysler automatic transmissions and automatic transaxles where a Mopar ATF PLUS, ATF+2 or ATF+3 fluid is specified. It is not recommended for use in transmissions specifying either DEXRON® or MERCON® type fluids. 2. Havoline Automatic Transmission Fluid ATF+3 has been registered with the Chrysler Corporation. Typical test data are average values only. Minor variations which do not affect product performance are to be expected in normal manufacturing. Notes: Chrysler, Mopar ATF PLUS, ATF+2, and ATF+3 are registered trademarks of DaimlerChrysler. DEXRON is a registered trademark of General Motors Corporation. MERCON is a registered trademark of Ford Motor Company. CPS Number: 221803; MSDS Number: 8630

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_ChevronTexaco-Havoline-ATF3-Automatic-Transmission-Fluid.php](http://www.lookpolymers.com/polymer_ChevronTexaco-Havoline-ATF3-Automatic-Transmission-Fluid.php)

Physical Properties	Metric	English	Comments
API Gravity	31.2 °	31.2 °	
Brookfield Viscosity	18000 cP @Temperature -40.0 °C	18000 cP @Temperature -40.0 °F	
Viscosity Measurement	188	188	Viscosity Index
Kinematic Viscosity at 40°C (104°F)	35.9 cSt	35.9 cSt	
Kinematic Viscosity at 100°C (212°F)	7.6 cSt	7.6 cSt	

Thermal Properties	Metric	English	Comments
Pour Point	-48.0 °C	-54.4 °F	
Flash Point	194 °C	381 °F	

Descriptive Properties	Value	Comments
------------------------	-------	----------

Descriptive Properties	Value	Comments
------------------------	-------	----------

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China