

ChevronTexaco Havoline® MERCON®/DEXRON®-III Automatic Transmission Fluid

Category : Fluid , Lubricant

Material Notes:

Havoline Automatic Transmission Fluid MERCON/DEXRON-III delivers value through: Protection against the formation of lacquers, sludge, or other harmful deposits. Exceptional stability provided by excellent base oil and extra oxidation inhibitors. Quiet Performance, especially effective in reducing transmission "chatter". Fast circulation during cold weather and excellent lubricating body when hot. Havoline Automatic Transmission Fluid MERCON/DEXRON-III is the latest high performance, multipurpose, power transmission fluid approved under Mercon® and Dexron® specifications. It is developed for passenger car and light truck automatic transmissions. It is manufactured from select Group II base oils and additives that provide oxidation and thermal stability, friction control, load-carrying ability, corrosion and wear protection. It prevents the accumulation of deposits and the formation of sludge, varnish, and foam. Under the most severe operating conditions, Havoline Automatic Transmission Fluid MERCON/DEXRON-III: Maintains friction control for smooth shift action. Is specially formulated to prevent shudder. Retains low temperature fluidity and high temperature stability for long operating periods. Protects automatic transmission fluid coolers from corrosion. Practically eliminates transmission overhauls due to sludge, corrosion, wear of clutches and bands, gears and bearings, leakage past seals, and loss of frictional properties. Havoline Automatic Transmission Fluid MERCON/DEXRON-III is designed for use in General Motors Corporation transmissions that require a DEXRON-II, DEXRON-II or DEXRON-III fluid, and Ford Motor Company transmissions that require a MERCON fluid. It is also used as a light oil in compressors, pumps and hydraulic systems. Always check your owners manual to determine the proper automatic transmission fluid for your transmission. Ford transmissions manufactured after 1996 may require a MERCON V. Chrysler transmissions manufactured after 1996 require either ATF+3® or ATF+4®. Havoline Automatic Transmission Fluid MERCON V meets or exceeds: Manufacturers performance requirements Ford MERCON General Motors DEXRON-III Allison C4 Caterpillar TO-2 Denison P-46 Piston Pump Vickers Pump Voith DIWA Transmissions AF transmissions. Typical test data are average values only. Minor variations which do not affect product performance are to be expected in normal manufacturing. CPS Number: 221854; MSDS Number: 8654

Order this product through the following link:

http://www.lookpolymers.com/polymer_ChevronTexaco-Havoline-MERCONDEXRON-III-Automatic-Transmission-Fluid.php

Physical Properties	Metric	English	Comments
API Gravity	32.7 °	32.7 °	
Brookfield Viscosity	17000 cP @Temperature -40.0 °C	17000 cP @Temperature -40.0 °F	
Viscosity Measurement	172	172	Viscosity Index
Saybolt Viscosity at 100°F	180 SUS	180 SUS	
Saybolt Viscosity at 210°F	50.3 SUS	50.3 SUS	
Kinematic Viscosity at 40°C (104°F)	35.5 cSt	35.5 cSt	
Kinematic Viscosity at 100°C (212°F)	7.2 cSt	7.2 cSt	

Thermal Properties	Metric	English	Comments
Pour Point	-48.0 °C	-54.4 °F	
Flash Point	202 °C	396 °F	

Descriptive Properties	Value	Comments
Color	Red	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China