

ChevronTexaco Havoline® SAE 10W-30 Synthetic Blend Motor Oil

Category : Fluid , Lubricant

Material Notes:

Havoline Synthetic Blend Motor Oil is formulated with a combination of synthetic and premium quality conventional base oils and an advanced additive package.Havoline Synthetic Blend Motor Oil is recommended for all four-stroke gasoline engines used in passenger cars, light trucks, powerboats, motorcycles, and other mobile and stationary equipment. It is excellent for high-revving engines in small cars and light trucks. It was specially formulated for use in turbocharged engines. It meets: API Service Categories SL, SJ, SH, SG, Energy conserving for API SLILSAC GF-3Ford ESE-M2C 153-GGeneral Motors GM 6094MDepartment of Defense Commercial Item Description A-A-52306USDA H2Typical test data are average values only. Minor variations which do not affect product performance are to be expected in normal manufacturing. CPS Number: 222105; MSDS Number: 8601

Order this product through the following link:

http://www.lookpolymers.com/polymer_ChevronTexaco-Havoline-SAE-10W-30-Synthetic-Blend-Motor-Oil.php

| Physical Properties | Metric | English | Comments |
|--------------------------------------|-----------------------|-----------------------|-----------------|
| API Gravity | 30.2 ° | 30.2 ° | |
| Viscosity | 6400 cP | 6400 cP | Cold Crank |
| | @Temperature -25.0 °C | @Temperature -13.0 °F | oold ofdlik |
| Viscosity Measurement | 134 | 134 | Viscosity Index |
| Kinematic Viscosity at 40°C (104°F) | 76 cSt | 76 cSt | |
| Kinematic Viscosity at 100°C (212°F) | 11 cSt | 11 cSt | |
| Ash | 0.90 % | 0.90 % | Sulfated Ash |

| Thermal Properties | Metric | English | Comments |
|--------------------|----------|----------|----------|
| Pour Point | -39.0 °C | -38.2 °F | |
| Flash Point | 234 °C | 453 °F | |

| Component Elements Properties | Metric | English | Comments |
|-------------------------------|---------|---------|----------|
| Phosphorous, P | 0.098 % | 0.098 % | |
| Zinc, Zn | 0.109 % | 0.109 % | |

| Chemical Properties | Metric | English | Comments | |
|------------------------|--------|---------|------------|--|
| Total Base Number | 8.2 | 8.2 | ASTM D2896 | |
| | | | | |
| Descriptive Properties | | Value | Comments | |

Descriptive Properties

Value

Comments

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com Email : sales@lookpolymers.com Tel : +86 021-51131842 Mobile : +86 13061808058 Skype : lookpolymers Address : United North Road 215,Fengxian District, Shanghai City,China