

ChevronTexaco Havoline® SAE 10W-40 Motor Oil

Category: Fluid, Lubricant

Material Notes:

All grades of Havoline Motor Oils are formulated with high quality base stocks, a shear-stable viscosity index improver, and contain detergent, dispersant, wear control, antioxidant, corrosion inhibitor, and foam suppressant additives. Havoline Motor Oils are recommended for all four-stroke gasoline engines used in passenger cars, light trucks, powerboats, motorcycles, and other mobile and stationary equipment. They are excellent for high-revving engines in small cars and light trucks. All grades are specially formulated for use in both new and high-mileage cars, and in turbocharged as well as normally aspirated engines. SAE 10W-40 is still a very popular viscosity grade in warmer climates, though it is not recommended by most auto manufacturers for their late model vehicles. It is often recommended for older model cars that see regular high temperature operation. Typical test data are average values only. Minor variations which do not affect product performance are to be expected in normal manufacturing. CPS Number: 222191; MSDS Number: 8599

Order this product through the following link:

http://www.lookpolymers.com/polymer_ChevronTexaco-Havoline-SAE-10W-40-Motor-Oil.php

| Physical Properties | Metric | English | Comments | |
|--------------------------------------|-----------------------|-----------------------|-----------------|--|
| API Gravity | 30.3 ° | 30.3 ° | | |
| Viscosity | 6400 cP | 6400 cP | Cold Crank | |
| | @Temperature -25.0 °C | @Temperature -13.0 °F | | |
| Viscosity Measurement | 148 | 148 | Viscosity Index | |
| Kinematic Viscosity at 40°C (104°F) | 104 cSt | 104 cSt | | |
| Kinematic Viscosity at 100°C (212°F) | 14.8 cSt | 14.8 cSt | | |
| Ash | 0.90 % | 0.90 % | Sulfated Ash | |

| Thermal Properties | Metric | English | Comments |
|--------------------|----------|----------|----------|
| Pour Point | -34.0 °C | -29.2 °F | |
| Flash Point | 234 °C | 453 °F | |

| Component Elements Properties | Metric | English | Comments | |
|-------------------------------|---------|---------|----------|--|
| Phosphorous, P | 0.094 % | 0.094 % | | |
| Zinc, Zn | 0.103 % | 0.103 % | | |

| Chemical Properties | Metric | English | Comments |
|---------------------|--------|---------|------------|
| Total Base Number | 7.6 | 7.6 | ASTM D2896 |



Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China