

## ChevronTexaco Havoline® SAE 30 Motor Oil

Category : Fluid , Lubricant

**Material Notes:**

All grades of Havoline Motor Oils are formulated with high quality base stocks, a shear-stable viscosity index improver, and contain detergent, dispersant, wear control, antioxidant, corrosion inhibitor, and foam suppressant additives. Havoline Motor Oils are recommended for all four-stroke gasoline engines used in passenger cars, light trucks, powerboats, motorcycles, and other mobile and stationary equipment. They are excellent for high-revving engines in small cars and light trucks. All grades are specially formulated for use in both new and high-mileage cars, and in turbocharged as well as normally aspirated engines. SAE 30 and SAE 40 can be used in any engine application where an SAE 30 or 40 passenger car motor oil of API SL or any previous "S" category is recommended. They perform exceptionally well in small four-stroke engines found in lawn mowers, garden tractors, snow blowers, and in refrigeration or air-conditioning engines on trucks and buses. Typical test data are average values only. Minor variations which do not affect product performance are to be expected in normal manufacturing. CPS Number: 222193; MSDS Number: 8599

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_ChevronTexaco-Havoline-SAE-30-Motor-Oil.php](http://www.lookpolymers.com/polymer_ChevronTexaco-Havoline-SAE-30-Motor-Oil.php)

Physical Properties	Metric	English	Comments
API Gravity	29.4 °	29.4 °	
Viscosity Measurement	108	108	Viscosity Index
Kinematic Viscosity at 40°C (104°F)	82 cSt	82 cSt	
Kinematic Viscosity at 100°C (212°F)	10.3 cSt	10.3 cSt	
Ash	0.90 %	0.90 %	Sulfated Ash

Thermal Properties	Metric	English	Comments
Pour Point	-33.0 °C	-27.4 °F	
Flash Point	250 °C	482 °F	

Component Elements Properties	Metric	English	Comments
Phosphorous, P	0.094 %	0.094 %	
Zinc, Zn	0.103 %	0.103 %	

Chemical Properties	Metric	English	Comments
Total Base Number	7.6	7.6	ASTM D2896

**Contact Songhan Plastic Technology Co.,Ltd.**

**Website : [www.lookpolymers.com](http://www.lookpolymers.com)**

**Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)**

**Tel : +86 021-51131842**

**Mobile : +86 13061808058**

**Skype : lookpolymers**

**Address : United North Road 215,Fengxian District, Shanghai City,China**