

ChevronTexaco Havoline® SAE 5W-20 Motor Oil

Category: Fluid, Lubricant

Material Notes:

All grades of Havoline Motor Oils are formulated with high quality base stocks, a shear-stable viscosity index improver, and contain detergent, dispersant, wear control, antioxidant, corrosion inhibitor, and foam suppressant additives. Havoline Motor Oils are recommended for all four-stroke gasoline engines used in passenger cars, light trucks, powerboats, motorcycles, and other mobile and stationary equipment. They are excellent for high-revving engines in small cars and light trucks. All grades are specially formulated for use in both new and high-mileage cars, and in turbocharged as well as normally aspirated engines. SAE 5W-20 provides optimum fuel economy and durability performance. Typical test data are average values only. Minor variations which do not affect product performance are to be expected in normal manufacturing. CPS Number: 222197; MSDS Number: 8599

Order this product through the following link:

http://www.lookpolymers.com/polymer_ChevronTexaco-Havoline-SAE-5W-20-Motor-Oil.php

Physical Properties	Metric	English	Comments
API Gravity	32.3°	32.3°	
Viscosity	5200 cP	5200 cP	Cold Crank
	@Temperature -30.0 °C	@Temperature -22.0 °F	
Viscosity Measurement	148	148	Viscosity Index
Kinematic Viscosity at 40°C (104°F)	45.5 cSt	45.5 cSt	
Kinematic Viscosity at 100°C (212°F)	8.0 cSt	8.0 cSt	
Ash	0.90 %	0.90 %	Sulfated Ash

Thermal Properties	Metric	English	Comments
Pour Point	-33.0 °C	-27.4 °F	
Flash Point	238 °C	460 °F	

Component Elements Properties	Metric	English	Comments
Phosphorous, P	0.094 %	0.094 %	
Zinc, Zn	0.112 %	0.112 %	

Chemical Properties	Metric	English	Comments
Total Base Number	8.5	8.5	ASTM D2896

Contact Songhan Plastic Technology Co.,Ltd.



Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China