

ChevronTexaco Havoline® SAE 5W-40 Synthetic Motor Oil

Category : Fluid , Lubricant

Material Notes:

Havoline Synthetic Motor Oil is recommended for all four-stroke gasoline engines used in passenger cars, sport utility vehicles, and light trucks. 5W-40 meets: API Service Categories SL/CF, SJ/CFACEA A3/B3BMW Longlife 98Mercedes Benz 229.1PorscheVolkswagen 502.00 and 505.00Volvo SMB 22-3Typical test data are average values only. Minor variations which do not affect product performance are to be expected in normal manufacturing. CPS Number: 222100; MSDS Number: 8602

Order this product through the following link:

http://www.lookpolymers.com/polymer_ChevronTexaco-Havoline-SAE-5W-40-Synthetic-Motor-Oil.php

Physical Properties	Metric	English	Comments
API Gravity	32.8 °	32.8 °	
Viscosity	5000 cP @Temperature -30.0 °C	5000 cP @Temperature -22.0 °F	Cold Crank
Viscosity Measurement	158	158	Viscosity Index
Kinematic Viscosity at 40°C (104°F)	87.7 cSt	87.7 cSt	
Kinematic Viscosity at 100°C (212°F)	13.7 cSt	13.7 cSt	
Ash	1.2 %	1.2 %	Sulfated Ash

Thermal Properties	Metric	English	Comments
Pour Point	-51.0 °C	-59.8 °F	
Flash Point	222 °C	432 °F	

Component Elements Properties	Metric	English	Comments
Phosphorous, P	0.098 %	0.098 %	
Zinc, Zn	0.103 %	0.103 %	

Chemical Properties	Metric	English	Comments
Total Base Number	8.8	8.8	ASTM D2896

Descriptive Properties	Value	Comments
Noack Volatility, wt%	8	250°C, 1 h

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China