## ChevronTexaco Havoline® SAE 85W-140 Gear Oil

Category : Fluid , Lubricant

## Material Notes:

Havoline Gear Oils are multipurpose lubricants. They are made from paraffinic base stocks and contain a carefully balanced additive package to provide maximum gear protection and long lubricant life. The sulfur-phosphorus extreme pressure additives used in Havoline Gear Oils provide superior thermal and oxidation stability.Recommended for use in all spiral bevel and hypoid differentials, power dividers, and oil lubricated steering axle wheel bearings. The multiviscosity characteristics allow use in equipment operating over a broad ambient temperature range. Havoline Gear Oils meet the performance requirements of API Service Categories MT-1 and GL-5, MIL-PRF-2105E, Mack GO-J, USDA H2.Typical test data are average values only. Minor variations which do not affect product performance are to be expected in normal manufacturing. CPS Number: 222272; MSDS Number: 8600

## Order this product through the following link:

http://www.lookpolymers.com/polymer\_ChevronTexaco-Havoline-SAE-85W-140-Gear-Oil.php

Physical Properties	Metric	English	Comments
API Gravity	25.9 °	25.9 °	
Brookfield Viscosity	102000 cP	102000 cP	
	@Temperature -12.0 °C	@Temperature 10.4 °F	
Viscosity Measurement	95	95	Viscosity Index
Saybolt Viscosity at 100°F	1819 SUS	1819 SUS	
Saybolt Viscosity at 210°F	124 SUS	124 SUS	
Kinematic Viscosity at 40°C (104°F)	341 cSt	341 cSt	
Kinematic Viscosity at 100°C (212°F)	25 cSt	25 cSt	

Mechanical Properties	Metric	English	Comments
Four Ball Extreme Pressure, Weld Load	315 kg	695 lb (mass)	ASTM D 2783
Timken Test	29500 g	65.0 lb	OK Load

Thermal Properties	Metric	English	Comments	
Pour Point	-15.0 °C	5.00 °F		
Flash Point	229 °C	444 °F		

Descriptive Properties	Value	Comments
Load Weld Index, kg	50	ASTM D 2783



## Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com Email : sales@lookpolymers.com Tel : +86 021-51131842 Mobile : +86 13061808058 Skype : lookpolymers Address : United North Road 215,Fengxian District, Shanghai City,China