

ChevronTexaco Havoline® TC-W3® Two-Cycle Engine Oil

Category : Fluid , Lubricant

Material Notes:

Havoline Two-Cycle Engine Oil TC-W3 is recommended as a premium lubricant for use in two-stroke engines where the latest TC-W3 or earlier general purpose lubricants are recommended. These applications include outboard engines, snowmobiles, motorcycles, lawn mowers, scooters, golf carts, chain saws, and other equipment. It is well suited for engines using oil injection systems with fuel/oil mixture ratios of up to 150:1. Meets:NMMA TC W3ISO-L EGB (JASO FB)API TCTypical test data are average values only. Minor variations which do not affect product performance are to be expected in normal manufacturing. CPS Number: 221896; MSDS Number: 8629

Order this product through the following link:

http://www.lookpolymers.com/polymer_ChevronTexaco-Havoline-TC-W3-Two-Cycle-Engine-Oil.php

Physical Properties	Metric	English	Comments
API Gravity	31.4 °	31.4 °	
Brookfield Viscosity	5500 cP	5500 cP	
	@Temperature -25.0 °C	@Temperature -13.0 °F	
Viscosity Measurement	119	119	Viscosity Index
Kinematic Viscosity at 40°C (104°F)	46.5 cSt	46.5 cSt	
Kinematic Viscosity at 100°C (212°F)	7.3 cSt	7.3 cSt	

Thermal Properties	Metric	English	Comments
Pour Point	-30.0 °C	-22.0 °F	
Flash Point	95.0 °C	203 °F	

Chemical Properties	Metric	English	Comments
Total Base Number	3.8	3.8	ASTM D2896

Descriptive Properties	Value	Comments
Ounces of oil to add	1 to 2	per gallon, 100:1 Ratio
	2 to 3	per gallon, 50:1 Ratio
	4	per gallon, 32:1 Ratio
	5 to 6	per gallon, 24:1 Ratio
	8	per gallon, 16:1 Ratio, 1 Gallon

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China