

ChevronTexaco Heavy Duty Synthetic Automatic Transmission Fluid

Category : Fluid , Lubricant

Material Notes:

Texaco Synthetic Automatic Transmission Fluid Heavy Duty delivers value through: Extended drains of up to four times that of a conventional automatic transmission fluid. Protection against the formation of lacquers, sludge, or other harmful deposits. Exceptional stability provided by excellent base oil and extra oxidation inhibitors. Fast circulation during cold weather and excellent lubricating qualities when hot. Optimized friction characteristics for smooth shifting and efficient power transfer. Texaco Synthetic Automatic Transmission Fluid Heavy Duty is engineered to meet the performance requirements of Allison TES 295 for severe duty and extended drain intervals. It is manufactured from synthetic base oils and additives that provide oxidation and thermal stability, friction control, load-carrying ability, corrosion and wear protection. It prevents the accumulation of deposits and the formation of sludge, varnish, and foam. Texaco Synthetic Automatic Transmission Fluid Heavy Duty has excellent low temperature flow properties and enhanced protection against viscosity breakdown. Under the most severe operating conditions, this fluid: Maintains friction control for smooth shift action Retains low temperature fluidity and high temperature stability for long operating periods. Provides excellent antiwear protection. Greatly extends the time to transmission overhauls due to sludge, corrosion, wear of clutches and bands, gears and bearings, leakage past seals, and loss of frictional properties. Texaco Synthetic Automatic Transmission Fluid Heavy Duty is specially engineered for heavy duty automatic truck and bus transmissions operating in extended service. It is also acceptable for use in passenger car applications requiring Ford MERCON® or General Motors DEXRON®-III. Texaco Synthetic Automatic Transmission Fluid Heavy Duty meets or exceeds manufacturers performance requirements: Allison C-4 Ford MERCON General Motors DEXRON-III Voith ZF (for extended drain intervals) Texaco Synthetic Automatic Transmission Fluid Heavy Duty has the following qualifications: Allison C-4 Pending Ford MERCON M000602 General Motors DEXRON-III G-34090 Voith G607ZF TE-ML 14B Do not use in high pressure systems in the vicinity of flames, sparks and hot surfaces. Use only in well ventilated areas. Keep container closed. Do not use in breathing air apparatus or medical equipment. Typical test data are average values only. Minor variations which do not affect product performance are to be expected in normal manufacturing. CPS Number: 221128; MSDS Number: 11488

Order this product through the following link:

http://www.lookpolymers.com/polymer_ChevronTexaco-Heavy-Duty-Synthetic-Automatic-Transmission-Fluid.php

Physical Properties	Metric	English	Comments
API Gravity	32.7 °	32.7 °	
Brookfield Viscosity	11400 cP @Temperature -40.0 °C	11400 cP @Temperature -40.0 °F	
Viscosity Measurement	184	184	Viscosity Index
Saybolt Viscosity at 100°F	181 SUS	181 SUS	
Saybolt Viscosity at 210°F	51 SUS	51 SUS	
Kinematic Viscosity at 40°C (104°F)	36 cSt	36 cSt	
Kinematic Viscosity at 100°C (212°F)	7.5 cSt	7.5 cSt	

Thermal Properties	Metric	English	Comments
Pour Point	-48.0 °C	-54.4 °F	
Flash Point	228 °C	442 °F	

Descriptive Properties	Value	Comments
Color	Red	
FZG Gear Wear Test	12	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China