

ChevronTexaco Hot Punch Compound H

Category : Fluid , Lubricant , Calcium Gellant

Material Notes:

Texaco Hot Punch Compound H is a dark, semi-fluid calcium soap thickened grease designed for use as a die lubricant. It contains graphite and telc, which enhance its lubricity. Typical test data are average values only. Minor variations which do not affect product performance are to be expected in normal manufacturing. Notes: Determined on mineral oil extracted by vacuum filtration. CPS Number: 221979; MSDS Number: 9020

Order this product through the following link:

http://www.lookpolymers.com/polymer_ChevronTexaco-Hot-Punch-Compound-H.php

Physical Properties	Metric	English	Comments
Solids Content	43 %	43 %	
Saybolt Viscosity at 100°F	3775 SUS	3775 SUS	See Note 1.
Saybolt Viscosity at 210°F	148 SUS	148 SUS	See Note 1.
Kinematic Viscosity at 40°C (104°F)	685 cSt	685 cSt	See Note 1.
Kinematic Viscosity at 100°C (212°F)	30 cSt	30 cSt	See Note 1.

Mechanical Properties	Metric	English	Comments
Penetration P(0), 1/10 mm	415	415	Unworked, 25°C (77°F)

Thermal Properties	Metric	English	Comments
Flash Point	260 °C	500 °F	See Note 1.

Descriptive Properties	Value	Comments
Color	Black	
Texture	Smooth	
Thickener, %	1.5	Calcium

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China