

## ChevronTexaco ISO 100 Machine Oil AW

Category : Fluid , Lubricant

**Material Notes:**

**Features**Chevron Machine Oils AW are premium quality lubricants.They provide excellent antiwear protection, oxidation and corrosion inhibition, and foam and aeration suppression.They are excellent multipurpose oils for all types of lubricant applications where a premium antiwear lubricant in their ISO viscosity grade is required, such as an AGMA Gear Lubricant or general machinery lubrication.All grades have excellent demulsibility. Chevron Machine Oils AW have excellent thermal and oxidation stability.They have a high viscosity index to assure good film strength between metal surfaces under moderate loads and temperatures. This film strength is further enhanced by the antiwear additive protection. The foam and aeration suppressant allows the quick release of entrained air, also improving film strength.

**Applications**Chevron Machine Oils AW are recommended for hydraulic equipment reduction gears, reciprocating air compressors, plain and antifriction bearings, and circulating oil systems where an ISO 100, 150, 220, or 320 grade is required.Chevron Machine Oils AW meet the requirements of ANSI/AGMA 9005-D94, Industrial Gear Lubrication, for gear lubrication as rust and oxidation inhibited gear oils.Chevron Machine Oils AW are registered with NSF International and are acceptable as lubricants where there is no possibility of food contact (H2) in and around food processing areas. The NSF Nonfood Compounds Registration Program is a continuation of the USDA product approval and listing program, which is based on meeting regulatory requirements of appropriate use, ingredient review and labeling verification.Do not use in high pressure systems in the vicinity of flames, sparks and hot surfaces. Use only in well ventilated areas. Keep container closed.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_ChevronTexaco-ISO-100-Machine-Oil-AW.php](http://www.lookpolymers.com/polymer_ChevronTexaco-ISO-100-Machine-Oil-AW.php)

Physical Properties	Metric	English	Comments
API Gravity	30.5 °	30.5 °	
Viscosity Measurement	100	100	Viscosity Index; ASTM D2270
Saybolt Viscosity at 100°F	495 SUS	495 SUS	
Saybolt Viscosity at 210°F	64 SUS	64 SUS	
Kinematic Viscosity at 40°C (104°F)	95 cSt	95 cSt	ASTM D445
Kinematic Viscosity at 100°C (212°F)	11 cSt	11 cSt	ASTM D445
Oxidative Stability	>= 2000 hour	>= 2000 hour	Hours to 2.0 mg KOH/g acid number; ASTM D943

Thermal Properties	Metric	English	Comments
Pour Point	-15.0 °C	5.00 °F	ASTM D97
Flash Point	250 °C	482 °F	ASTM D92

**Contact Songhan Plastic Technology Co.,Ltd.**

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China