

ChevronTexaco ISO 22 Form Oil

Category : Fluid , Lubricant

Material Notes:

Features Chevron Form Oil is a high quality, lightly compounded lubricant which will do an excellent job as a concrete form oil where customers desire a quick clean break from the forms. Chevron Form Oil is a light colored oil manufactured using specially refined base oils. These base oils possess excellent natural low pour points, good "metal wetting" characteristics, and good natural film strength. Chevron Form Oil contains an oiliness additive that improves film strength under boundary lubrication. **Applications** Chevron Form Oil is an excellent concrete form wetting agent. It can be used on any form where a release agent is recommended. Chevron Form Oil is especially recommended for the manufacture of precast concrete structures, concrete pipe, and precast concrete curbs and beams. Chevron Form Oil, with the oiliness additive, does an excellent job in aluminum polishing. Chevron Form Oil is recommended for use by the steel industry as a rust preventive on sheet and plate steel, wire, and cold drawn bar stock in warehouse storage.

Order this product through the following link:

http://www.lookpolymers.com/polymer_ChevronTexaco-ISO-22-Form-Oil.php

Physical Properties	Metric	English	Comments
API Gravity	26.8 °	26.8 °	
Viscosity Measurement	56	56	Viscosity Index; ASTM D2270
Saybolt Viscosity at 100°F	121 SUS	121 SUS	
Saybolt Viscosity at 210°F	40.1 SUS	40.1 SUS	
Kinematic Viscosity at 40°C (104°F)	23.1 cSt	23.1 cSt	ASTM D445
Kinematic Viscosity at 100°C (212°F)	4.1 cSt	4.1 cSt	ASTM D445

Thermal Properties	Metric	English	Comments
Pour Point	-40.0 °C	-40.0 °F	ASTM D97
Flash Point	185 °C	365 °F	ASTM D92

Descriptive Properties	Value	Comments
Wetting Agent, %	4.5	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China