

ChevronTexaco ISO 460 Cylinder Oil

Category: Fluid, Lubricant

Material Notes:

Chevron Cylinder Oil is a steam cylinder oil. Chevron Cylinder Oil is designed to meet the needs of nonemulsifying cylinder oils. Chevron Cylinder Oils has excellent demulsifying characteristics required in steam systems where the oil is recirculated. Applications Chevron Cylinder Oil is recommended where complete demulsibility is required. This is especially important where exhaust steam is returned to the boiler. Good demulsibility assures efficient equipment operation by reducing the risks of contamination, thereby preventing boiler tube fouling and improving heat transfer efficiency.

Order this product through the following link:

http://www.lookpolymers.com/polymer_ChevronTexaco-ISO-460-Cylinder-Oil.php

Physical Properties	Metric	English	Comments
API Gravity	25.4°	25.4°	
Viscosity Measurement	95	95	Viscosity Index; ASTM D2270
Saybolt Viscosity at 100°F	2341 SUS	2341 SUS	
Saybolt Viscosity at 210°F	144 SUS	144 SUS	
Kinematic Viscosity at 40°C (104°F)	437 cSt	437 cSt	ASTM D445
Kinematic Viscosity at 100°C (212°F)	29.4 cSt	29.4 cSt	ASTM D445

Thermal Properties	Metric	English	Comments
Pour Point	-14.0 °C	6.80 °F	ASTM D97
Flash Point	310 °C	590 °F	ASTM D92

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China