

ChevronTexaco Journaltex® HD 57

Category : Fluid , Lubricant

Material Notes:

Texaco Journaltex HD 57 delivers value through:Excellent lubricity characteristics imparted by the additive package minimizes friction to help prevent premature bearing failure.Good rust protection – Effective inhibitor package prevents rusting of surfaces exposed to water.Water separability – Texaco Journaltex HD 57 separates easily from water.Good shear stabilityExcellent air release by foam inhibitor hastens the release of foam and entrained air.Texaco Journaltex HD 57 is manufactured from high viscosity index, low pour point base oils for use on suspension bearings. It contains an additive package that resists rust and corrosion and protects journal bearings during the critical break-in period by minimizing friction in heaving loaded bearings.Texaco Journaltex HD 57 is designed to lubricate locomotive traction motor suspension bearings and plain railcar journal bearings. It is also recommended for lubricating tractor motor suspension bearings, truck center plates, plain journal bearing waste saturation and pad lubrication or free oiling.It meets the requirements of:AAR M-963-84 Specification for Journal Box Lubricating OilsGE D50E14 and EMD 1002 specifications covering suspension bearings.Typical test data are average values only. Minor variations which do not affect product performance are to be expected in normal manufacturing. CPS Number: 220674; MSDS Number: 8985

Order this product through the following link:

http://www.lookpolymers.com/polymer_ChevronTexaco-Journaltex-HD-57.php

Physical Properties	Metric	English	Comments
API Gravity	31 °	31 °	
Viscosity Measurement	117	117	Viscosity Index
Saybolt Viscosity at 100°F	320 SUS	320 SUS	
Saybolt Viscosity at 210°F	56 SUS	56 SUS	
Kinematic Viscosity at 40°C (104°F)	60.9 cSt	60.9 cSt	
Kinematic Viscosity at 100°C (212°F)	8.7 cSt	8.7 cSt	

Thermal Properties	Metric	English	Comments
Pour Point	-39.0 °C	-38.2 °F	
Flash Point	237 °C	459 °F	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China