

## ChevronTexaco L Metal Protective Oil L

Category: Fluid, Lubricant

## **Material Notes:**

Texaco Metal Protective Oil L delivers value through: Excellent short-term rust protection — After evaporation of the solvent, a highly protective, nondrying oil film remains which provides a higher level of protection against corrosion than lower viscosity products. The corrosion inhibitors in the oil resist chemical attack by water, other fluids and particulate matter. Minimum drippage — Viscosity of the oil is low enough to enable ready drain-off of excess oil. High volatility of the solvent ensures rapid evaporation, minimizing post-application dripping. Easy removal — Oil film is readily soluble in petroleum solvent or kerosene to enable easy removal when required. Texaco Metal Protective Oil L is a higher viscosity, rust protective oil designed for the temporary rust protection of steel in covered storage or packaged shipment. It contains corrosion inhibitors and is diluted with a petroleum solvent for ease of application. Texaco Metal Protective Oil L is recommended for: Use as temporary protection of plain and galvanized steel sheet, coils, bars, rods and tubes during undercover storage, protected shipment or interprocess handling Protection against yellow-line stain that tends to form on stacked sheets or coiled strip; white rust on galvanized steel; red rustMay be applied by brush, roller, dip, or spray. Typical test data are average values only. Minor variations which do not affect product performance are to be expected in normal manufacturing. CPS Number: 221052; MSDS Number: 10690

Order this product through the following link:

http://www.lookpolymers.com/polymer\_ChevronTexaco-L-Metal-Protective-Oil-L.php

Physical Properties	Metric	English	Comments
API Gravity	27.1 °	27.1°	
Saybolt Viscosity at 100°F	92 SUS	92 SUS	
Kinematic Viscosity at 40°C (104°F)	17 cSt	17 cSt	

Thermal Properties	Metric	English	Comments	
Pour Point	-23.0 °C	-9.40 °F		
Flash Point	88.0 °C	190 °F		

## Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China