

ChevronTexaco Rykon® NLGI 1 Premium Grease EP

Category : Fluid , Lubricant , Urea Gellant

Material Notes:

FeaturesChevron Rykon Premium Grease EP is a high quality, water resistant, extreme pressure, multipurpose lubricating grease. It is manufactured using highly refined, select high viscosity index base oils, and a polyurea thickener. It is green in color and smooth in texture.

ApplicationsChevron Rykon Premium Grease EP is recommended for: automotive applications including heavy duty truck wheel bearings, universal joints, water pumps, and idler pulleys roller bearings operating at 135 to 177°C (275 to 350°F) that require a high temperature extreme pressure grease.

Chevron Rykon Premium Grease EP is registered with NSF and is acceptable as a lubricant where there is no possibility of food contact (H2) in and around food processing areas. The NSF Nonfood Compounds Registration Program is a continuation of the USDA product approval and listing program, which is based on meeting regulatory requirements of appropriate use, ingredient review and labeling verification.

Order this product through the following link:

http://www.lookpolymers.com/polymer_ChevronTexaco-Rykon-NLGI-1-Premium-Grease-EP.php

Physical Properties	Metric	English	Comments
Viscosity Measurement	99	99	Viscosity Index; ASTM D2270
Saybolt Viscosity at 100°F	787 SUS	787 SUS	
Saybolt Viscosity at 210°F	80 SUS	80 SUS	
Kinematic Viscosity at 40°C (104°F)	150 cSt	150 cSt	ASTM D445
Kinematic Viscosity at 100°C (212°F)	15 cSt	15 cSt	ASTM D445

Mechanical Properties	Metric	English	Comments
Penetration	277	277	Worked

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	177 °C	351 °F	
Minimum Service Temperature, Air	-34.0 °C	-29.2 °F	
Dropping Point	260 °C	500 °F	

Descriptive Properties	Value	Comments
Bearing Rust	Pass	
Color	Green	
Texture	Smooth	
Thickener, % / type	12 / Polyurea	

Descriptive Properties	Value	Comments
------------------------	-------	----------

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com
Email : sales@lookpolymers.com
Tel : +86 021-51131842
Mobile : +86 13061808058
Skype : lookpolymers
Address : United North Road 215,Fengxian District, Shanghai City,China