

ChevronTexaco Supreme SAE 10W-30 Motor Oil

Category : Fluid , Lubricant

Material Notes:

FeaturesChevron Supreme Motor Oils are premium quality automotive engine oils. Chevron Supreme Motor Oils SAE 5W-20, 5W-30, 10W-30, 10W-40, and 20W-50 are formulated with ISO-SYN™ base stocks, a shear-stable viscosity index improver, and contain detergent, dispersant, wear control, antioxidant, corrosion inhibitor, and foam suppressant additives. The high viscosity index of Chevron Supreme Motor Oils ensures low viscosities at low temperatures for easy cold starting and rapid warm-up and high viscosities at high temperatures for fuel economy, oil economy, and effective protective films for engine parts. Their antiwear additive provide excellent wear protection of critical engine parts. A high level of dispersancy in Chevron Supreme Motor Oils protects against deposit and sludge formation in stop-and-go driving and sustained high temperature operation, and protects against corrosion. Their excellent high temperature oxidation stability prevents viscosity increase and oil gelling in the crankcase. They keep PCV systems clean to maintain smooth engine performance.

ApplicationsChevron Supreme Motor Oils are recommended for all four-stroke gasoline engines used in passenger cars, light trucks, power boats, motorcycles, and other mobile and stationary equipment. They are excellent for high revving engines in small cars and light trucks. All grades are specially formulated for using in turbocharged engines. SAE 10W-30 is recommended for many older vehicles and a few late model cars and trucks, often those with larger 6-cylinder and V-8 and/or high performance engines. SAE 10W-30 provides improved fuel economy relative to heavier viscosity grades.

Order this product through the following link:

http://www.lookpolymers.com/polymer_ChevronTexaco-Supreme-SAE-10W-30-Motor-Oil.php

Physical Properties	Metric	English	Comments
API Gravity	30.4 °	30.4 °	
Viscosity	5800 cP @Temperature -25.0 °C	5800 cP @Temperature -13.0 °F	Cold Crank
Viscosity Measurement	135	135	Viscosity Index; ASTM D2270
Kinematic Viscosity at 40°C (104°F)	73.5 cSt	73.5 cSt	ASTM D445
Kinematic Viscosity at 100°C (212°F)	10.8 cSt	10.8 cSt	ASTM D445
Ash	0.90 %	0.90 %	Sulfated Ash wt%

Thermal Properties	Metric	English	Comments
Pour Point	-35.0 °C	-31.0 °F	ASTM D97
Flash Point	232 °C	450 °F	ASTM D92

Component Elements Properties	Metric	English	Comments
Phosphorous, P	0.094 %	0.094 %	
Zinc, Zn	0.103 %	0.103 %	

Component Elements Properties	Metric	English	Comments
Chemical Properties	Metric	English	Comments
Total Base Number	7.4	7.4	ASTM D2896

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China