

## ChevronTexaco Supreme SAE 20W-50 Motor Oil

Category : Fluid , Lubricant

### Material Notes:

**Features**Chevron Supreme Motor Oils are premium quality automotive engine oils. Chevron Supreme Motor Oils SAE 5W-20, 5W-30, 10W-30, 10W-40, and 20W-50 are formulated with ISO-SYN™ base stocks, a shear-stable viscosity index improver, and contain detergent, dispersant, wear control, antioxidant, corrosion inhibitor, and foam suppressant additives. The high viscosity index of Chevron Supreme Motor Oils ensures low viscosities at low temperatures for easy cold starting and rapid warm-up and high viscosities at high temperatures for fuel economy, oil economy, and effective protective films for engine parts. Their antiwear additive provide excellent wear protection of critical engine parts. A high level of dispersancy in Chevron Supreme Motor Oils protects against deposit and sludge formation in stop-and-go driving and sustained high temperature operation, and protects against corrosion. Their excellent high temperature oxidation stability prevents viscosity increase and oil gelling in the crankcase. They keep PCV systems clean to maintain smooth engine performance.

**Applications**Chevron Supreme Motor Oils are recommended for all four-stroke gasoline engines used in passenger cars, light trucks, power boats, motorcycles, and other mobile and stationary equipment. They are excellent for high revving engines in small cars and light trucks. All grades are specially formulated for using in turbocharged engines. SAE 20W-50 is recommended primarily for older engines for use in high temperature and heavy duty operations such as towing heavy trailers at highway speeds or up inclines for long periods of time. It is also recommended for some high performance engines used in racing and rallying.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_ChevronTexaco-Supreme-SAE-20W-50-Motor-Oil.php](http://www.lookpolymers.com/polymer_ChevronTexaco-Supreme-SAE-20W-50-Motor-Oil.php)

Physical Properties	Metric	English	Comments
API Gravity	28.9 °	28.9 °	
Viscosity	8000 cP @Temperature -15.0 °C	8000 cP @Temperature 5.00 °F	Cold Crank
Viscosity Measurement	122	122	Viscosity Index; ASTM D2270
Kinematic Viscosity at 40°C (104°F)	176 cSt	176 cSt	ASTM D445
Kinematic Viscosity at 100°C (212°F)	19 cSt	19 cSt	ASTM D445
Ash	0.90 %	0.90 %	Sulfated Ash wt%

Thermal Properties	Metric	English	Comments
Pour Point	-29.0 °C	-20.2 °F	ASTM D97
Flash Point	258 °C	496 °F	ASTM D92

Component Elements Properties	Metric	English	Comments
Phosphorous, P	0.094 %	0.094 %	
Zinc, Zn	0.103 %	0.103 %	

Component Elements Properties	Metric	English	Comments
Chemical Properties	Metric	English	Comments
Total Base Number	7.4	7.4	ASTM D2896

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China