

ChevronTexaco Supreme SAE 5W-40 Synthetic Motor Oil

Category : Fluid , Lubricant

Material Notes:

Features Chevron Supreme 100% Synthetic Motor Oils are designed for those drivers who demand the ultimate in engine protection. They provide an extra measure of protection for the investment in a sport utility vehicle (SUV), high performance, or luxury car. Chevron Supreme 100% Synthetic Motor Oils give improved protection to high output, supercharged and turbocharged performance vehicles. Chevron Supreme 100% Synthetic Motor Oils are formulated using 100% synthetic base stocks for the best performance. The improved volatility and stability of synthetic base stocks give reduced oil consumption, faster engine starting (especially in cold weather), and extremely fast lubrication of all moving parts compared to conventional mineral oils. In addition, a special blend of additives protects the engine against harmful deposits and wear. SAE 5W-40 provides the broadest range of protection of the three Supreme Synthetic Motor oils. It is specifically formulated to meet European requirements and is an officially approved product by BMW, Mercedes Benz, Porsche, and Volkswagen. It meets the requirements of API SL/CF.

Applications Chevron Supreme Synthetic Motor Oils are recommended for all four-stroke gasoline engines in passenger cars, sport utility vehicles, and light trucks.

Order this product through the following link:

http://www.lookpolymers.com/polymer_ChevronTexaco-Supreme-SAE-5W-40-Synthetic-Motor-Oil.php

Physical Properties	Metric	English	Comments
API Gravity	32.8 °	32.8 °	
Viscosity	5000 cP @Temperature -305 °C	5000 cP @Temperature -517 °F	Cold Crank
Viscosity Measurement	158	158	Viscosity Index; ASTM D2270
Kinematic Viscosity at 40°C (104°F)	87.7 cSt	87.7 cSt	ASTM D445
Kinematic Viscosity at 100°C (212°F)	13.7 cSt	13.7 cSt	ASTM D445
Ash	1.2 %	1.2 %	Sulfated Ash wt%

Thermal Properties	Metric	English	Comments
Pour Point	<= -51.0 °C	<= -59.8 °F	ASTM D97
Flash Point	222 °C	432 °F	ASTM D92

Component Elements Properties	Metric	English	Comments
Phosphorous, P	0.098 %	0.098 %	
Zinc, Zn	0.103 %	0.103 %	

Chemical Properties	Metric	English	Comments

Total Base Number	8.8	8.8	ASTM D2896
Chemical Properties	Metric	English	Comments

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com
Email : sales@lookpolymers.com
Tel : +86 021-51131842
Mobile : +86 13061808058
Skype : lookpolymers
Address : United North Road 215,Fengxian District, Shanghai City,China