

ChevronTexaco TC-W3 2-Cycle Oil

Category : Fluid , Lubricant

Material Notes:

FeaturesChevron 2-Cycle Oil TC-W3 is a high quality two-stroke engine lubricant that delivers excellent performance in water-cooled and air-cooled applications. It is formulated to provide excellent lubrication and deposit control in a wide range of applications. Chevron 2-Cycle Oil TC-W3 contains a special ashless detergent designed to minimize piston rings from sticking to keep the engine operating smoothly and efficiently. Chevron 2-Cycle Oil TC W3 will keep the engine clean of deposits and will also protect the pistons from scuffing and pre-ignition problems. To enhance storage and transportation safety, Chevron 2-Cycle Oil TC-W3 contains a high flash solvent. This solvent also allows good mixing with gasoline at very low temperatures. It is dyed teal blue for easy identification of fuel-oil mixtures in pre-mixed applications.

ApplicationsChevron 2-Cycle Oil TC-W3 is recommended as a premium lubricant for use in two-stroke engines where the latest TC-W3 or earlier general purpose lubricants are recommended. There applications include outboard engines, snowmobiles, motorcycles, lawn mowers, scooters, golf carts, chain saws, and other two-stroke powered equipments. Chevron 2-Cycle Oil TC-W3 is well suited for engines using oil injection systems with fuel/oil mixture ratios of up to 150:1. Chevron 2-cycle Oil TC W3 has excellent low temperature mixing characteristics that make it very suitable for use in cold climate conditions.

Order this product through the following link:

http://www.lookpolymers.com/polymer_ChevronTexaco-TC-W3-2-Cycle-Oil.php

Physical Properties	Metric	English	Comments
API Gravity	31.4 °	31.4 °	
Brookfield Viscosity	5500 cP	5500 cP	
	@Temperature -25.0 °C	@Temperature -13.0 °F	
Viscosity Measurement	119	119	Viscosity Index; ASTM D2270
Kinematic Viscosity at 40°C (104°F)	46.5 cSt	46.5 cSt	ASTM D445
Kinematic Viscosity at 100°C (212°F)	7.3 cSt	7.3 cSt	ASTM D445
Ash	0.00 %	0.00 %	Sulfated Ash wt%

Thermal Properties	Metric	English	Comments
Pour Point	-30.0 °C	-22.0 °F	ASTM D97
Flash Point	95.0 °C	203 °F	ASTM D92

Chemical Properties	Metric	English	Comments
Total Base Number	3.8	3.8	ASTM D2896

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China