

ChevronTexaco TDH® W Oil

Category : Fluid , Lubricant

Material Notes:

Texaco TDH oils deliver value through: Lower operating costs – By delivering or exceeding the performance of fluids supplied by equipment manufacturers, helps in avoiding the cost of generally more expensive fluids and thereby lowers overall operating costs. Longer equipment life – Special additives protect metal surfaces against scuffing and wear even under severe operating conditions leading to increased equipment life. Lower inventory cost – One fluid does the job of a full range of mobile hydraulic systems. Can replace multiple products and free up shelf space too! Minimizing weather and storage concerns – Protects against rust and corrosion of highly finished precision parts when operating in humid conditions and during seasonal shutdown periods. Reduced downtime – Good compatibility with seals, O-rings, and packing materials maintains their good condition and keeps leakage at a minimum. Smoother operation – By eliminating brake "chatter" and transmission "slip" they assure quiet and efficient action of brakes and transmission. More reliable operation – Formulation keeps metal parts clean and free of varnish and sludge deposits that could result in premature breakdown. Texaco TDH oils are high quality, multifunctional fluids, specially formulated for use in transmissions, final drives, wet brakes, and hydraulic systems of tractors and other equipment employing a common fluid reservoir. They are formulated with high quality base stocks, a viscosity index improver, oxidation and corrosion inhibitors, antiwear and film strength additives, an antifoaming agent, and a pour point depressant. The distinctive orange color of Texaco TDH Oil allows for easy product identification and leak detection. Texaco TDH Oil W is undyed. Texaco TDH oils meet the needs of modern tractors for a combination lubricant. They perform many functions, such as lubrication of the transmission and final drive, and serve as hydraulic fluids to operate power steering units, brakes, implements, and attachments. Furthermore, Texaco TDH oils eliminate brake "chatter" and excessive brake facing wear, assure smooth operation of clutch packs and wet brakes, provide excellent shifting action, provide superior rust and corrosion protection for vital parts, minimize leakage because of good compatibility with seals, O-rings, and packing materials. They prevent sludge and varnish formation, protect metal surfaces against scuffing and wear, and provide outstanding lubrication for spur, helical, and spiral bevel final drive gears. Texaco TDH oils are compatible with equipment manufacturers proprietary fluids and other fluids of this type. Typical test data are average values only. Minor variations which do not affect product performance are to be expected in normal manufacturing. CPS Number: 221888; MSDS Number: 11013

Order this product through the following link:

http://www.lookpolymers.com/polymer_ChevronTexaco-TDH-W-Oil.php

Physical Properties	Metric	English	Comments
API Gravity	31.9 °	31.9 °	
Brookfield Viscosity	17000 cP @Temperature -35.0 °C	17000 cP @Temperature -31.0 °F	
Viscosity Measurement	185	185	Viscosity Index
Saybolt Viscosity at 100°F	174.2 SUS	174.2 SUS	
Saybolt Viscosity at 210°F	50.6 SUS	50.6 SUS	
Kinematic Viscosity at 40°C (104°F)	34.4 cSt	34.4 cSt	
Kinematic Viscosity at 100°C (212°F)	7.3 cSt	7.3 cSt	

Physical Properties	Metric	English	Comments
Thermal Properties	Metric	English	Comments
Pour Point	-48.0 °C	-54.4 °F	
Flash Point	214 °C	417 °F	

Descriptive Properties	Value	Comments
Color	Pale	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China