

ChevronTexaco THF W

Category : Fluid , Lubricant

Material Notes:

FeaturesChevron THF W is a high quality, multifunctional fluid, specially formulated for low temperature use in transmissions, final drives, wet brakes, and hydraulic systems of tractors and other equipment employing a common fluid reservoir. It is formulated with high quality base stocks, a viscosity index improver, oxidation and corrosion inhibitors, antiwear and film strength additives, an antifoaming agent, and a pour point depressant. **Applications**Chevron THF W is specifically formulated to meet the requirements of Jophn Deere J20D. It is recommended for use in equipment that operates at low ambient temperatures and as a multifunctional fluid in all types of farm tractors and equipment. It can also be used in any application which calls for the following OEM lubricant specifications: AGCO-improved power fluid 821XL John Deere-J20D New Holland-ESN-M2C134-A/B/C/D, FNHA 2 C 201 Massey Ferguson-M1135, M1141, M1143 White Farm Equipment-Q-1826 Case Corporation-JIC-143, JIC-145, MS 1206, MS 1207, MS 1209, MS 1210 (TCH) Oliver-Type 55 Minneapolis-Moline-Fluids Caterpillar-TO-2 Renk-Bus Automatic Transmission Fluid 873, 874 A/B Kubota-UDT International Harvester-B6 Deutz-Allis 821XL

Order this product through the following link:

http://www.lookpolymers.com/polymer_ChevronTexaco-THF-W.php

Physical Properties	Metric	English	Comments
API Gravity	31.9 °	31.9 °	
Brookfield Viscosity	17000 cP	17000 cP	
	@Temperature -40.0 °C	@Temperature -40.0 °F	
Viscosity Measurement	185	185	Viscosity Index; ASTM D2270
Saybolt Viscosity at 100°F	174.2 SUS	174.2 SUS	
Saybolt Viscosity at 210°F	50.6 SUS	50.6 SUS	
Kinematic Viscosity at 40°C (104°F)	34.4 cSt	34.4 cSt	ASTM D445
Kinematic Viscosity at 100°C (212°F)	7.3 cSt	7.3 cSt	ASTM D445

Thermal Properties	Metric	English	Comments
Pour Point	-48.0 °C	-54.4 °F	ASTM D97
Flash Point	214 °C	417 °F	ASTM D92

Descriptive Properties	Value	Comments
Color	Pale	

Contact Songhan Plastic Technology Co.,Ltd.Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China