

ChevronTexaco Taro® 13 ZF SAE 40

Category : Fluid , Lubricant

Material Notes:

Texaco Tar 13 ZF is a high dispersant, zinc free oil designed for turbocharged and naturally aspirated diesel engines. Typical test data are average values only. Minor variations which do not affect product performance are to be expected in normal manufacturing. CPS Number: 222208; MSDS Number: 8799

Order this product through the following link:

http://www.lookpolymers.com/polymer_ChevronTexaco-Taro-13-ZF-SAE-40.php

Physical Properties	Metric	English	Comments
API Gravity	28.4 °	28.4 °	
Viscosity Measurement	98	98	Viscosity Index
Kinematic Viscosity at 40°C (104°F)	148 cSt	148 cSt	
Kinematic Viscosity at 100°C (212°F)	15 cSt	15 cSt	
Ash	1.3 %	1.3 %	Sulfated Ash

Thermal Properties	Metric	English	Comments
Pour Point	-15.0 °C	5.00 °F	
Flash Point	270 °C	518 °F	

Chemical Properties	Metric	English	Comments
Total Base Number	13	13	ASTM D2896

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China