

ChevronTexaco Taro® 30 DP SAE 30

Category: Fluid, Lubricant

Material Notes:

Texaco Taro 30 DP delivers value through: Wear protection — Performance results in the latest design medium speed trunk piston diesel engines have shown that the high level of alkalinity of this lubricating oil controls cylinder liner wear effectively and protects bearings from corrosion. High performance antiwear additives provide excellent protection against adhesive wear for cams, camshaft and bearings.Reduced foaming and improved water tolerance - Texaco Taro 30 DP provides a high degree of water tolerance and antifoam protection. Prevents deposits - Provides exceptionally clean crankcase interiors, keeps oil control rings clean and prevents deposit formation throughout the engine. Extends oil filter cleaning intervals. Has excellent insolubles control. Oxidation stability — Texaco Taro 30 DP withstands high thermal stress of high output trunk piston engines and reduces undercrown deposits. Lubricating qualities of the oil remain at a very high level over long periods of use and engine parts are protected from the corrosive effects of oil oxidation products. Rust protection - Effective inhibitor package prevents corrosion of engine parts when the engine is not in operation. Balanced additive combination — Ensures high quality performance with excellent overall protection. Provides minimum maintenance and down time, long engine life, and economical operating costs. Texaco Taro 30 DP is a high performance high alkaline diesel engine oil for medium speed trunk piston diesel engines burning residual fuels with a maximum sulfur level of 4%. Texaco Taro 30 DP is blended from high quality base oils and additives that provide an extra margin of protection against ring sticking, piston deposits and wear under the most severe operating conditions. Taro 30 DP has very good viscosity control when used in severe high temperature service and its excellent alkalinity retention characteristics prevent corrosive wear over long periods of operation. The unique detergent and dispersant additive system provides outstanding piston cleanliness as well as good heavy fuel related contaminants handling characteristics. This results in significant reduction of both "hot" (piston lands and grooves, piston undercrown, purifier preheaters) and "cold" (crankcase, cambox, rocker area, fuel pumps, purifier bowl) deposits. Texaco Taro 30 DP is recommended for all types of trunk piston diesel engines burning MDO or low sulphur heavy fuels with a sulphur level of 4%. Texaco Taro 30 DP meets the requirements of all major marine diesel engine manufacturers. Texaco Taro 30 DP meets the performance requirements of API Service Category CF. Typical test data are average values only. Minor variations which do not affect product performance are to be expected in normal manufacturing. CPS Number: 221674; MSDS Number: 8753

Order this product through the following link:

http://www.lookpolymers.com/polymer_ChevronTexaco-Taro-30-DP-SAE-30.php

Physical Properties	Metric	English	Comments
API Gravity	27.3°	27.3°	
Viscosity Measurement	102	102	Viscosity Index
Kinematic Viscosity at 40°C (104°F)	94 cSt	94 cSt	
Kinematic Viscosity at 100°C (212°F)	11 cSt	11 cSt	
Ash	3.7 %	3.7 %	Sulfated Ash, mass %

Pour Point -18.0 °C -0.400 °F	Thermal Properties	Metric	English	Comments	
	Pour Point	-18.0 °C	-0.400 °F		



Elash Fount Thermal Properties	230 °C Metric	English	Comments	
Chemical Properties	Metric	English	Comments	
Total Base Number	30	30	ASTM D2896	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China