

ChevronTexaco Taro® 50 XL SAE 40

Category : Fluid , Lubricant

Material Notes:

Texaco Taro 50 XL delivers value through:Wear protection – Performance results in the latest design medium speed trunk piston diesel engines have shown that the high level of alkalinity of this lubricating oil controls cylinder liner wear effectively and protects bearings from corrosion. High performance antiwear additives provide excellent protection against adhesive wear for cams, camshaft and bearings.Reduced foaming and improved water tolerance – Texaco Taro 50 XL provides a high degree of water tolerance and antifoam protection.Prevents deposits – Provides exceptionally clean crankcase interiors, keeps oil control rings clean and prevents deposit formation throughout the engine. Extends oil filter cleaning intervals. Has excellent insolubles control.Oxidation stability – Texaco Taro 50 XL withstands high thermal stress of high output trunk piston engines and reduces undercrown deposits. Lubricating qualities of the oil remain at a very high level over long periods of use and engine parts are protected from the corrosive effects of oil oxidation products.Rust protection – Effective inhibitor package prevents corrosion of engine parts when the engine is not in operation.Balanced additive combination – Ensures high quality performance with excellent overall protection. Provides minimum maintenance and down time, long engine life, and economical operating costs.Texaco Taro 50 XL is a high performance very high alkaline diesel engine oil for medium speed trunk piston diesel engines burning residual fuels with a maximum sulfur level of 5%.Texaco Taro 50 XL is blended from high quality base oils and additives that provide an extra margin of protection against ring sticking, piston deposits and wear under the most severe operating conditions.Taro 50 XL has very good viscosity control when used in severe high temperature service and its excellent alkalinity retention characteristics prevent corrosive wear over long periods of operation. The unique detergent and dispersant additive system provides outstanding piston cleanliness as well as good heavy fuel related contaminants handling characteristics. This results in significant reduction of both "hot" (piston lands and grooves, piston undercrown, purifier preheaters) and "cold" (crankcase, cambox, rocker area, fuel pumps, purifier bowl) deposits.Texaco Taro 50 XL is recommended for all types of trunk piston diesel engines burning residual fuels with a maximum sulfur level of 5% and with low oil consumption.Texaco Taro 50 XL meets the performance requirements of API Service Category CF.Typical test data are average values only. Minor variations which do not affect product performance are to be expected in normal manufacturing. CPS Number: 221879; MSDS Number: 8753

Order this product through the following link:

http://www.lookpolymers.com/polymer_ChevronTexaco-Taro-50-XL-SAE-40.php

Physical Properties	Metric	English	Comments
API Gravity	24.6 °	24.6 °	
Viscosity Measurement	100	100	Viscosity Index
Kinematic Viscosity at 40°C (104°F)	128 cSt	128 cSt	
Kinematic Viscosity at 100°C (212°F)	14 cSt	14 cSt	
Ash	5.9 %	5.9 %	Sulfated Ash, mass %

Thermal Properties	Metric	English	Comments
Pour Point	-15.0 °C	5.00 °F	

Flash Point Thermal Properties	240 °C Metric	464 °F English	Comments
Chemical Properties	Metric	English	Comments
Total Base Number	50	50	ASTM D2896

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China