

## ChevronTexaco Thuban® SAE 250

Category : Fluid , Lubricant

**Material Notes:**

Typical test data are average values only. Minor variations which do not affect product performance are to be expected in normal manufacturing. CPS Number: 220994; MSDS Number: 8801

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_ChevronTexaco-Thuban-SAE-250.php](http://www.lookpolymers.com/polymer_ChevronTexaco-Thuban-SAE-250.php)

Physical Properties	Metric	English	Comments
API Gravity	23.7 °	23.7 °	
Viscosity Measurement	96	96	Viscosity Index
Saybolt Viscosity at 100°F	6381 SUS	6381 SUS	
Saybolt Viscosity at 210°F	270.8 SUS	270.8 SUS	
Kinematic Viscosity at 40°C (104°F)	1172 cSt	1172 cSt	
Kinematic Viscosity at 100°C (212°F)	55.7 cSt	55.7 cSt	

Thermal Properties	Metric	English	Comments
Pour Point	-9.00 °C	15.8 °F	
Flash Point	324 °C	615 °F	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China