

ChevronTexaco Torque Fluid

Category : Fluid , Lubricant

Material Notes:

Chevron Torque Fluid is a high performance hydraulic fluid designed for use in transmissions and hydraulic systems requiring a fluid meeting the Allison C4 specification. It is manufactured using highly refined base oils, oxidation and corrosion inhibitors, antiwear and extreme pressure agents, and foam suppressant. Applications Chevron Torque Fluid is recommended for use in Allison Powershift transmissions, some torque converters, and hydraulic systems requiring an Allison C4 fluid. It is also recommended for heavy duty truck and tractor automatic transmissions requiring a fluid of its viscosity and general characteristics, and for mobile hydraulic systems where operating requirements are too severe for straight mineral oils.

Order this product through the following link:

http://www.lookpolymers.com/polymer_ChevronTexaco-Torque-Fluid.php

Physical Properties	Metric	English	Comments
API Gravity	31.3 °	31.3 °	
Viscosity	3000 cP @Temperature -20.0 °C	3000 cP @Temperature -4.00 °F	Cold Crank
Viscosity Measurement	110	110	Viscosity Index; ASTM D2270
Saybolt Viscosity at 100°F	236 SUS	236 SUS	
Saybolt Viscosity at 210°F	50 SUS	50 SUS	
Kinematic Viscosity at 40°C (104°F)	45.8 cSt	45.8 cSt	ASTM D445
Kinematic Viscosity at 100°C (212°F)	7.0 cSt	7.0 cSt	ASTM D445

Thermal Properties	Metric	English	Comments
Pour Point	-38.0 °C	-36.4 °F	ASTM D97
Flash Point	219 °C	426 °F	ASTM D92

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China