

Chosun Refractories BATN-8 Gas Purging Refractory

Category : Ceramic , Oxide , Aluminum Oxide

Material Notes:

Information provided by Chosun Refractories via Korea Institute of Ceramic Engineering and Technology (KICET).

Order this product through the following link:

http://www.lookpolymers.com/polymer_Chosun-Refractories-BATN-8-Gas-Purging-Refractory.php

Physical Properties	Metric	English	Comments
Bulk Density	2.80 - 2.90 g/cc	0.101 - 0.105 lb/in ³	
Porosity	23 - 27 %	23 - 27 %	

Mechanical Properties	Metric	English	Comments
Compressive Strength	<= 19.6 MPa	<= 2840 psi	Cold Crushing Strength

Thermal Properties	Metric	English	Comments
CTE, linear	5.00 $\mu\text{m}/\text{m}\cdot^\circ\text{C}$ @Temperature 1000 °C	2.78 $\mu\text{in}/\text{in}\cdot^\circ\text{F}$ @Temperature 1830 °F	

Component Elements Properties	Metric	English	Comments
Al2O3	85 - 90 %	85 - 90 %	
Cr2O3	1.0 - 2.0 %	1.0 - 2.0 %	

Descriptive Properties	Value	Comments
Main Application	Porous Nozzle, High durability for steel infiltration	
Permeability(? ,cm/? ,sec,h2o ,cm)	1.3	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China