

Chosun Refractories LW-28 Special Insulating Firebrick

Category: Ceramic

Material Notes:

Information provided by Chosun Refractories via Korea Institute of Ceramic Engineering and Technology (KICET).

Order this product through the following link:

http://www.lookpolymers.com/polymer_Chosun-Refractories-LW-28-Special-Insulating-Firebrick.php

Physical Properties	Metric	English	Comments
Bulk Density	>= 0.800 g/cc	>= 0.0289 lb/in³	

Mechanical Properties	Metric	English	Comments
Compressive Strength	<= 0.981 MPa	<= 142 psi	Cold Crushing Strength

Thermal Properties	Metric	English	Comments
Thermal Conductivity	>= 0.2675 W/m-K	>= 1.854 BTU-in/hr- ft²-°F	
	@Temperature 350 °C	@Temperature 662 °F	

Component Elements Properties	Metric	English	Comments	
Fe2O3	>= 1.0 %	>= 1.0 %		

Descriptive Properties	Value	Comments
Main Applications	Various Furnace inside lining	
Temp.(?) Reheating Shrinkage less than 0.5%	1,500	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China