

## **Colorite Polymers CS6033UL Wire and Cable Jacket Vinyl Compound**

Category: Polymer, Thermoplastic, Vinyl (PVC), PVC, Wire and Cable Grade

## **Material Notes:**

Description: Colorite specialty wire and cable compounds feature low smoke properties, excellent flame retardance, low temperature flexibility, and resistance to abrasion and chemicals. All are available in UL and non-UL grades. In addition, the engineering-grade thermoplastic elastomers we offer can stand up to the most demanding applications . . . while providing the most desirable performance characteristics at a cost that's more affordable than "ordinary" elastomers. Typical Applications: UL T, TW 60° oil. UL 62 Class 11Information provided by Colorite Polymers.

## Order this product through the following link:

http://www.lookpolymers.com/polymer\_Colorite-Polymers-CS6033UL-Wire-and-Cable-Jacket-Vinyl-Compound.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.33 g/cc	1.33 g/cc	ASTM D792
Loss On Ignition	25.5 %	25.5 %	ASTM 2863

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	80	80	10 sec; ASTM D2240
Tensile Strength, Ultimate	15.2 MPa	2200 psi	ASTM D412
Elongation at Break	300 %	300 %	ASTM D412

Thermal Properties	Metric	English	Comments	
Maximum Service Temperature, Air	60.0°C	140 °F		
Brittleness Temperature	-30.0 °C	-22.0 °F	ASTM D746	

## **Contact Songhan Plastic Technology Co.,Ltd.**

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China