

## ConocoPhillips 32 Ultra-Clean Super Hydraulic Oil

Category : Fluid , Lubricant

### Material Notes:

Description: Conoco Ultra-Clean Super Hydraulic Oils have the same high performance characteristics of regular Super Hydraulic Oils with the added advantage of a guaranteed ISO cleanliness code of 14/11. Careful attention to particle control leads to high cleanliness fluids appropriate for use in critical applications. Ultra-Clean Super Hydraulic Oils are recommended for use in a variety of high-pressure mobile and stationary hydraulic systems utilizing vane, piston or gear pumps, especially where particle contamination can create operational problems. By virtue of their composition, Ultra-Clean Super Hydraulic Oils have the same performance rating and meet the same approval criteria as Super Hydraulic Oils, thus meeting Denison Hydraulics' HF-0 requirements and Cincinnati Machine's P-68 (ISO 32), P-70 (46) and P-69 (68) specifications. Similarly, Ultra-Clean Super Hydraulic Oil exceeds Vickers M-2950-S, Vickers I-286-S and U.S. Steel 127 and 136 requirements. Ultra-Clean Super Hydraulic Oils are available in ISO Viscosity Grades 32, 46, 68 and 100. Information provided by ConocoPhillips.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_ConocoPhillips-32-Ultra-Clean-Super-Hydraulic-Oil.php](http://www.lookpolymers.com/polymer_ConocoPhillips-32-Ultra-Clean-Super-Hydraulic-Oil.php)

Physical Properties	Metric	English	Comments
Density	0.862 g/cc	0.0311 lb/in <sup>3</sup>	
Viscosity Measurement	103	103	Viscosity Index
Saybolt Viscosity at 100°F	165 SUS	165 SUS	
Saybolt Viscosity at 210°F	44 SUS	44 SUS	
Kinematic Viscosity at 40°C (104°F)	31 cSt	31 cSt	
Kinematic Viscosity at 100°C (212°F)	5.4 cSt	5.4 cSt	
Oxidative Stability	4500 hour	4500 hour	ASTM D 943
ASTM Color	0.50	0.50	

Mechanical Properties	Metric	English	Comments
Four Ball Wear	0.450 mm	0.0177 in	

Thermal Properties	Metric	English	Comments
Pour Point	-37.2 °C	-35.0 °F	
Flash Point	216 °C	420 °F	

Electrical Properties	Metric	English	Comments
Dielectric Strength	35.0 kV/mm	889 kV/in	No thickness given

Descriptive Properties	Value	Comments
Emulsion Characteristics (40-40-0)	10 minutes	
FZG	Pass 10 Stages	
ISO Cleanliness Code	14/11	

**Contact Songhan Plastic Technology Co.,Ltd.**

Website : [www.lookpolymers.com](http://www.lookpolymers.com)  
Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)  
Tel : +86 021-51131842  
Mobile : +86 13061808058  
Skype : lookpolymers  
Address : United North Road 215,Fengxian District, Shanghai City,China