

## ConocoPhillips 6+ Brick Grease NLGI No. 6+

Category : Fluid , Lubricant , Lithium Gellant , Organic Soap Gellant

**Material Notes:**

Description: Conoco Brick Grease is a hard, amber-colored, smooth-textured, lithium-based grease made in block or brick form. Brick Grease provides a high melting point block grease with good heat resistance. It is designed for the lubrication of open heavy-duty bearings equipped with open well top feed grease collars, such as: Kiln, trunnion and support wall bearings; Ball, tube, rod and comped mill bearings; Paper machine dryer section; Cement mills, jack shaft bearings, crushers, rolling mills, rubber compounding mills, etc.; Kiln dryers; Dehydrators

Information provided by ConocoPhillips.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_ConocoPhillips-6-Brick-Grease-NLGI-No-6.php](http://www.lookpolymers.com/polymer_ConocoPhillips-6-Brick-Grease-NLGI-No-6.php)

Physical Properties	Metric	English	Comments
Viscosity Measurement	81	81	Viscosity Index (Base Oil Property)
Saybolt Viscosity at 100°F	450 - 550 SUS	450 - 550 SUS	Base Oil Property
Saybolt Viscosity at 210°F	55 - 65 SUS	55 - 65 SUS	Base Oil Property
Kinematic Viscosity at 40°C (104°F)	105 cSt	105 cSt	Base Oil
Kinematic Viscosity at 100°C (212°F)	10.5 cSt	10.5 cSt	Base Oil

Mechanical Properties	Metric	English	Comments
Penetration P(0), 1/10 mm	45 - 65	45 - 65	

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	129 °C	265 °F	
Minimum Service Temperature, Air	-12.2 °C	10.0 °F	
Dropping Point	196 °C	385 °F	

Descriptive Properties	Value	Comments
Color	Medium Amber	
Soap Type (Thickener)	Lithium	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China