

ConocoPhillips Conoco® El Mar® Ashless Supreme Oil, SAE Viscosity Grade 30

Category : Fluid , Lubricant

Material Notes:

Conoco® El Mar Ashless Supreme is a premium quality, ashless, dispersant-detergent gas engine oil designed for use in naturally aspirated and turbocharged 2-stroke cycle natural gas engines. Engines operating in this type of service typically are found on crude oil and gas transmission pipelines, electrical power generators, gas compressors, irrigation water pumps and well drilling rigs. El Mar Ashless Supreme is formulated with advanced, field-proven performance additives to meet the rigorous lubrication demands of modern, fuel-efficient, low-emission gas engines. It provides excellent resistance to oxidation and nitration, protects against ring and liner wear, minimizes the formation of sludge and piston deposits for outstanding engine cleanliness, and protects against corrosion. The absence of ash-forming additives results in very clean intake ports to help maintain peak engine performance, and also helps extend spark plug life in spark-ignited gas engines. Applications: 2-stroke cycle and some 4-stroke cycle natural gas engines where the manufacturer specifies an ashless gas engine oil El Mar Ashless Supreme is recommended for use in natural gas engines manufactured by: AjaxClimax Colt-Fairbanks Morse Cooper-Bessemer Dresser Clark Dresser Rand (Category I & II) Worthington Features/Benefit: Field-proven performance in providing outstanding engine cleanliness Ashless formulation helps minimize port deposits High dispersancy protects against sludge and varnish formation Excellent resistance to oxidation and nitration Protects against scuffing and wear Protects against rust and corrosion Does not contain any bright stock, which can cause harmful carbon deposits Information provided by ConocoPhillips.

Order this product through the following link:

http://www.lookpolymers.com/polymer_ConocoPhillips-Conoco-El-Mar-Ashless-Supreme-Oil-SAE-Viscosity-Grade-30.php

| Physical Properties | Metric | English | Comments |
|--------------------------------------|------------|---------------------------|-------------------------|
| Specific Gravity | 0.883 g/cc | 0.883 g/cc | 60°F |
| Density | 0.882 g/cc | 0.0319 lb/in ³ | |
| Viscosity Measurement | 100 | 100 | Viscosity Index |
| Kinematic Viscosity at 40°C (104°F) | 92.8 cSt | 92.8 cSt | |
| Kinematic Viscosity at 100°C (212°F) | 11 cSt | 11 cSt | |
| Ash | <= 0.010 % | <= 0.010 % | Sulfated Ash; ASTM D874 |
| ASTM Color | 3.0 | 3.0 | ASTM D1500 |

| Thermal Properties | Metric | English | Comments |
|--------------------|----------|----------|----------|
| Pour Point | -30.0 °C | -22.0 °F | |
| Flash Point | 260 °C | 500 °F | COC |

| Component Elements Properties | Metric | English | Comments |
|-------------------------------|---------|---------|----------|
| Phosphorous, P | 0.067 % | 0.067 % | |

| Chemical Properties | Metric | English | Comments |
|---------------------|--------|---------|------------|
| Total Base Number | 1.3 | 1.3 | ASTM D2896 |

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China