

## ConocoPhillips Conoco® El Mar® Geo Low Ash Oil, SAE Viscosity Grade 30

Category : Fluid , Lubricant

### Material Notes:

Conoco® El Mar GEO Oil is a high-quality, non-detergent, ashless gas engine oil designed primarily for use in Ajax 2-stroke cycle natural gas engines. The SAE 15W-40 viscosity grade meets the low-temperature viscosity requirements of Ajax engines where cold starts and frequent start/stop cycles may be encountered. El Mar GEO Oil is formulated to provide excellent resistance to oxidation and nitration, protect against ring and liner wear, minimize the formation of sludge and piston deposits for excellent engine cleanliness, and protect against corrosion. The absence of ash-forming additives results in clean intake ports to help maintain peak engine performance, and also helps extend spark plug life in spark-ignited gas engines. This oil is formulated to meet the requirements of gas engines equipped with exhaust after treatment devices.

**Applications:** 2 Cooper-Ajax 2-stroke cycle natural gas engines (SAE 15W-40) Older, horizontal-type 2-stroke cycle natural gas engines, such as those manufactured by Cooper-Bessemer and Worthington (SAE 30/40) El Mar GEO Oil is approved for use under the following OEM specification: DuPont Specification A4V4

**Features/Benefit:** Ashless formulation helps minimize port deposits Protects against sludge and varnish formation Excellent resistance to oxidation and nitration Protects against scuffing and wear Protects against rust and corrosion Excellent water-separating properties Low carbon-forming tendency Compatible with emissions system catalysts Does not contain any bright stock, which can cause harmful carbon deposits

Information provided by ConocoPhillips

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_ConocoPhillips-Conoco-El-Mar-Geo-Low-Ash-Oil-SAE-Viscosity-Grade-30.php](http://www.lookpolymers.com/polymer_ConocoPhillips-Conoco-El-Mar-Geo-Low-Ash-Oil-SAE-Viscosity-Grade-30.php)

Physical Properties	Metric	English	Comments
Specific Gravity	0.885 g/cc	0.885 g/cc	60°F
Density	0.883 g/cc	0.0319 lb/in <sup>3</sup>	
Viscosity Measurement	91	91	Viscosity Index
Kinematic Viscosity at 40°C (104°F)	133 cSt	133 cSt	
Kinematic Viscosity at 100°C (212°F)	13.1 cSt	13.1 cSt	
Ash	<= 0.010 %	<= 0.010 %	Sulfated Ash; ASTM D874
ASTM Color	3.0	3.0	ASTM D1500

Thermal Properties	Metric	English	Comments
Pour Point	-23.9 °C	-11.0 °F	
Flash Point	280 °C	536 °F	COC

Component Elements Properties	Metric	English	Comments
Phosphorous, P	0.0030 %	0.0030 %	

Chemical Properties	Metric	English	Comments
Total Acid Number	0.14	0.14	ASTM D974

Descriptive Properties	Value	Comments
Carbon Reside	0.05%	ASTM D524

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China