

ConocoPhillips Conoflex® 32 SRI Lubricant ISO

Category : Fluid , Lubricant

Material Notes:

Description: Conoco Conoflex SRI Lubricant is an excellent wire rope lubricant and preservative for any metal product, particularly when protecting from saltwater. It lubricates and preserves the wire ropes commonly found in shovels, draglines, winches, boom trucks, cable cars and ski lifts. It is a departure from the black asphaltic lubricants that traditionally have been used in this equipment. It flows easily at temperatures as low as -20°F (-29°C) and continues to lubricate in situations where traditional asphaltic lubricants fail. Conoflex SRI Lubricant penetrates cables rapidly to prevent rust and corrosion. It protects equipment exposed to freshwater or saltwater, such as offshore drilling rigs, ship and dock equipment, refineries and industrial plants. Ideal for protecting new metal parts in storage and shipment. It is also an excellent preservative for stored parts, tools and other equipment. Information provided by ConocoPhillips.

Order this product through the following link:

http://www.lookpolymers.com/polymer_ConocoPhillips-Conoflex-32-SRI-Lubricant-ISO.php

Physical Properties	Metric	English	Comments
Density	0.909 g/cc	0.0329 lb/in ³	
Viscosity Measurement	110	110	Viscosity Index
Saybolt Viscosity at 100°F	170 SUS	170 SUS	
Saybolt Viscosity at 210°F	46 SUS	46 SUS	
Kinematic Viscosity at 40°C (104°F)	33 cSt	33 cSt	
Kinematic Viscosity at 100°C (212°F)	5.6 cSt	5.6 cSt	

Thermal Properties	Metric	English	Comments
Pour Point	-37.2 °C	-35.0 °F	
Flash Point	188 °C	370 °F	

Descriptive Properties	Value	Comments
Color	Tan-Brown	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China