

ConocoPhillips HD Fleet™ 149 Engine Oil SAE 40

Category : Fluid , Lubricant

Material Notes:

Description: Conoco HD Fleet 149 Engine Oil is a high-quality, low ash API CF-2 single-grade oil recommended for high-output, two-stroke cycle diesel engines. It is formulated primarily for DD Series 149 engines operating under severe conditions, such as in mine haul trucks or for Series 149 Marine engines operating on low sulfur (

Order this product through the following link:

http://www.lookpolymers.com/polymer_ConocoPhillips-HD-Fleet-149-Engine-Oil-SAE-40.php

Physical Properties	Metric	English	Comments
API Gravity	28.6 °	28.6 °	
Viscosity Measurement	96	96	Viscosity Index
Kinematic Viscosity at 40°C (104°F)	155 cSt	155 cSt	
Kinematic Viscosity at 100°C (212°F)	14.9 cSt	14.9 cSt	
Ash	0.70 %	0.70 %	Sulfur
ASTM Color	3.5	3.5	

Thermal Properties	Metric	English	Comments
Pour Point	-21.1 °C	-6.00 °F	
Flash Point	260 °C	500 °F	

Chemical Properties	Metric	English	Comments
Total Base Number	7.2	7.2	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China