

ConocoPhillips Hydroclear® 10W Fluid 10W

Category : Fluid , Lubricant

Material Notes:

Description: Conoco Hydroclear PowerDrive Fluid meets the stringent performance requirements of powershift transmissions, final drives, and wet-disc brakes typically found in equipment manufactured by Caterpillar and Allison. Hydroclear PowerDrive Fluid meets the requirements of the Caterpillar TO-4 specification. The SAE 10W and 30 grades are approved as Allison C-4 transmission fluids, and the SAE 10W, 30 and 50 have been approved as a Komatsu KES 07.868.1 transmission oil. PowerDrive offers outstanding FZG gear-wear protection and Vickers 35VQ25 hydraulic-pump protection. Today's powershift transmissions, final drives and wet-disc brakes feature complex design and advanced materials. They require fluids that are specially formulated to enhance their performance. Hydroclear PowerDrive Fluid controls the friction in powershift transmissions, which employ as many as seven metallic and nonmetallic friction materials in the clutch pack. Its stable friction characteristics minimize brake noise, clutch slippage under heavy load, weakening of the binder in paper materials and embrittlement of elastomeric materials. Information provided by ConocoPhillips.

Order this product through the following link:

http://www.lookpolymers.com/polymer_ConocoPhillips-Hydroclear-10W-Fluid-10W.php

| Physical Properties | Metric | English | Comments |
|--------------------------------------|-----------------------|-----------------------|-----------------|
| API Gravity | 30.3 ° | 30.3 ° | |
| Viscosity | 3400 cP | 3400 cP | |
| | @Temperature -20.0 °C | @Temperature -4.00 °F | |
| Viscosity Measurement | 107 | 107 | Viscosity Index |
| Kinematic Viscosity at 40°C (104°F) | 41.6 cSt | 41.6 cSt | |
| Kinematic Viscosity at 100°C (212°F) | 6.5 cSt | 6.5 cSt | |
| Ash | 1.2 % | 1.2 % | Sulfur |

| Thermal Properties | Metric | English | Comments |
|--------------------|----------|----------|----------|
| Pour Point | -40.0 °C | -40.0 °F | |
| Flash Point | 224 °C | 435 °F | |

| Chemical Properties | Metric | English | Comments |
|---------------------|--------|---------|----------|
| Total Base Number | 7.5 | 7.5 | |

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China