

ConocoPhillips Hydroclear® 15W-40 Power-D E.O. 15W-40

Category : Fluid , Lubricant

Material Notes:

Description: Conoco Hydroclear Power-D Engine Oil, formulated from Conoco's premium hydrocracked base stock, protects diesel and gasoline engines against wear, deposits, varnish, rust and corrosion. These performance- proven, heavy-duty engine oils are recommended for both on- and off-road service, including construction, forestry, mining, marine and stationary power generation. They are also recommended for propane and compressed natural gas engines. In Power-D Engine Oil, the exclusive combination of hydrocracked base oils and unique high-performance additives offer excellent soot control, which results in cleaner engines, longer engine life and fewer drain intervals. Hydroclear Power-D Engine Oil SAE 15W40 exceeds the performance requirements of API CH-4; Mack EO-M; EO-M Plus; Cummins CES 20071, 20072, 20076, and 20077; and Volvo VDS and VDS-2, as well as the top EUROPEAN specifications. Hydroclear Power-D Engine Oil, in the appropriate viscosity grades, is recommended for use in most domestic and imported heavy-duty engines. Information provided by ConocoPhillips.

Order this product through the following link:

http://www.lookpolymers.com/polymer_ConocoPhillips-Hydroclear-15W-40-Power-D-EO-15W-40.php

Physical Properties	Metric	English	Comments
API Gravity	30.4 °	30.4 °	
Viscosity Measurement	139	139	Viscosity Index
Kinematic Viscosity at 40°C (104°F)	108 cSt	108 cSt	
Kinematic Viscosity at 100°C (212°F)	14.8 cSt	14.8 cSt	
Ash	1.35 %	1.35 %	Sulfur
ASTM Color	4.0	4.0	

Thermal Properties	Metric	English	Comments
Pour Point	-40.0 °C	-40.0 °F	
Flash Point	221 °C	430 °F	

Chemical Properties	Metric	English	Comments
Total Base Number	10.2	10.2	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China