

ConocoPhillips Hydroclear® 20W-50 High Performance Motor Oil SAE 20W-50

Category : Fluid , Lubricant

Material Notes:

Description: Conoco Hydroclear High Performance Motor Oil SAE 20W-50, formulated with premium base stocks, lubricates gasoline engines that operate under severe driving conditions. It is particularly recommended for high performance racing and rally driving by both domestic and foreign automobiles, including those equipped with turbochargers and superchargers where the manufacturer specifies an SAE 20W-50 motor oil. It is also recommended for motorcycles that require viscosity grade SAE 20W-50. Hydroclear High Performance Motor Oil exceeds the performance requirements of API Service SL. It protects engines against wear, rust and corrosion and against the formation of sludge or varnish deposits. Its stable viscosity protects vital engine parts – even at high temperatures. Information provided by ConocoPhillips.

Order this product through the following link:

http://www.lookpolymers.com/polymer_ConocoPhillips-Hydroclear-20W-50-High-Performance-Motor-Oil-SAE-20W-50.php

Physical Properties	Metric	English	Comments
API Gravity	30 °	30 °	
Viscosity	8800 cP	8800 cP	Cold-Cranking Viscosity
	@Temperature -15.0 °C	@Temperature 5.00 °F	
Viscosity	22000 cP	22000 cP	MRV TP-1
	@Temperature -20.0 °C	@Temperature -4.00 °F	
Viscosity Measurement	122	122	Viscosity Index
Saybolt Viscosity at 100°F	901 SUS	901 SUS	
Saybolt Viscosity at 210°F	86 SUS	86 SUS	
Kinematic Viscosity at 40°C (104°F)	173 cSt	173 cSt	
Kinematic Viscosity at 100°C (212°F)	18.8 cSt	18.8 cSt	
ASTM Color	3.5	3.5	

Thermal Properties	Metric	English	Comments
Pour Point	-32.8 °C	-27.0 °F	
Flash Point	210 °C	410 °F	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China