

ConocoPhillips Hydroclear® 220 Rock Oil

Category: Fluid, Lubricant

Material Notes:

Description: Conoco Hydroclear Rock Drill Oil is a high-quality, heavy-duty, extreme-pressure pneumatic tool lubricant formulated from premium Conoco hydrocracked base stocks. Hydroclear Rock Drill Oil is specially formulated with proprietary additive chemistry and is recommended for use in a variety of pneumatic tool applications which require extreme-pressure properties for protection of equipment under high-load conditions, tackiness for good adhesion to working surfaces, good atomization with low-fogging tendencies and excellent low temperature fluidity. Hydroclear Rock Drill Oil is specifically formulated for use in surface-mining equipment, high- and low-speed drills, jackhammers, paving breakers, vacuum pumps, track-type air drills and other similar applications. Hydroclear Rock Drill Oil can also be used effectively as a saw guide lubricant in lumber mill applications. Hydroclear Rock Drill Oil is available in seven viscosity grades, ISO 32-320, to meet the needs of most applications and operating conditions. Hydroclear Rock Drill Oil exceeds the lubricant specifications for Ingersoll-Rand and Gardner-Denver drilling equipment.Information provided by ConocoPhillips.

Order this product through the following link:

http://www.lookpolymers.com/polymer_ConocoPhillips-Hydroclear-220-Rock-Oil.php

Physical Properties	Metric	English	Comments
Density	0.887 g/cc	0.0320 lb/in³	
Viscosity Measurement	100	100	Viscosity Index
Saybolt Viscosity at 100°F	1195 SUS	1195 SUS	
Saybolt Viscosity at 210°F	99 SUS	99 SUS	
Kinematic Viscosity at 40°C (104°F)	226 cSt	226 cSt	
Kinematic Viscosity at 100°C (212°F)	19.5 cSt	19.5 cSt	
ASTM Color	5.0	5.0	

Mechanical Properties	Metric	English	Comments
Falex Load Test	1.13e+6 g	2500 lb	
Timken Test	27200 g	60.0 lb	

Thermal Properties	Metric	English	Comments
Pour Point	-17.8 °C	0.000 °F	
Flash Point	243 °C	470 °F	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com



Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China