

ConocoPhillips Hydroclear® 320 Circulating Oil

Category : Fluid , Lubricant

Material Notes:

Description: Conoco Hydroclear Circulating Oil is a high-quality, rust-inhibited circulating oil formulated from premium Conoco hydrocracked base stocks. Hydroclear Circulating Oil is specially formulated with proprietary additive chemistry and is recommended for use in a variety of bearing, mild-duty hydraulic and circulating oil applications which require a lubricant with rapid water separation, rust and corrosion protection and foam control. Hydroclear Circulating Oil is specifically formulated for use in backup roll bearings found in ferrous and nonferrous rolling mills, general-purpose bearing lubrication, circulating oil systems, "once through" oiling systems, seal oil applications and other similar end uses. Hydroclear Circulating Oil is available in ISO 150 and 320 viscosity grades. Information provided by ConocoPhillips.

Order this product through the following link:

http://www.lookpolymers.com/polymer_ConocoPhillips-Hydroclear-320-Circulating-Oil.php

Physical Properties	Metric	English	Comments
Density	0.890 g/cc	0.0322 lb/in ³	
Viscosity Measurement	95	95	Viscosity Index
Saybolt Viscosity at 100°F	1840 SUS	1840 SUS	
Saybolt Viscosity at 210°F	126 SUS	126 SUS	
Kinematic Viscosity at 40°C (104°F)	345 cSt	345 cSt	
Kinematic Viscosity at 100°C (212°F)	25.5 cSt	25.5 cSt	
ASTM Color	5.0	5.0	

Thermal Properties	Metric	English	Comments
Pour Point	-15.0 °C	5.00 °F	
Flash Point	277 °C	530 °F	

Descriptive Properties	Value	Comments
ASTM Rust A&B	Pass	
Emulsion Characteristics (40-40-0)	20 minutes	
Foam Control (Sequence I,II,II)	0-0-0	

Contact Songhan Plastic Technology Co.,Ltd.Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China