

ConocoPhillips Par® 68 Hydraulic Oil

Category : Fluid , Lubricant

Material Notes:

Description: Conoco Par Hydraulic Oil is an economical hydraulic oil designed to protect the hydraulic systems of underground mining equipment. It is available in ISO grades 68 and 100 and meets the performance requirements of the Hagglands-Denison HF-2 specification and U.S. Steel Specification 127 for extra-duty antiwear hydraulic fluids. It also meets the requirements of Joy, Simmons-Rand and other manufacturers of underground mining equipment. Information provided by ConocoPhillips.

Order this product through the following link:

http://www.lookpolymers.com/polymer_ConocoPhillips-Par-68-Hydraulic-Oil.php

Physical Properties	Metric	English	Comments
Density	0.877 g/cc	0.0317 lb/in ³	
Viscosity Measurement	90	90	Viscosity Index
Saybolt Viscosity at 100°F	332 SUS	332 SUS	
Saybolt Viscosity at 210°F	54 SUS	54 SUS	
Kinematic Viscosity at 40°C (104°F)	64 cSt	64 cSt	
Kinematic Viscosity at 100°C (212°F)	8.1 cSt	8.1 cSt	
Oxidative Stability	1500 hour	1500 hour	

Thermal Properties	Metric	English	Comments
Pour Point	-17.8 °C	0.000 °F	
Flash Point	207 °C	405 °F	

Descriptive Properties	Value	Comments
ASTM Foam Test	Pass	
ASTM Rust A&B	Pass	
Emulsion Characteristics (40-40-0)	15 minutes	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China