

## Cotronics Duralco™ 127 400°F (200°C) Graphite Filled Epoxy

Category : Polymer , Thermoset , Epoxy

**Material Notes:**

One component, graphite filled epoxy for low cost production applications. Can be used with automatic dispensing equipment.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Cotronics-Duralco-127-400F-200C-Graphite-Filled-Epoxy.php](http://www.lookpolymers.com/polymer_Cotronics-Duralco-127-400F-200C-Graphite-Filled-Epoxy.php)

Physical Properties	Metric	English	Comments
Viscosity	50000 cP	50000 cP	

Thermal Properties	Metric	English	Comments
Thermal Conductivity	3.60 W/m-K	25.0 BTU-in/hr-ft <sup>2</sup> -°F	
Maximum Service Temperature, Air	204 °C	400 °F	

Electrical Properties	Metric	English	Comments
Volume Resistivity	0.020 ohm-cm	0.020 ohm-cm	

Processing Properties	Metric	English	Comments
Cure Time	10.0 min	0.167 hour	
	@Temperature 162 °C	@Temperature 324 °F	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China