

Cotronics Resbond™ 908 High Temperature Ceramic Adhesive, Moisture Proof

Category : Ceramic

Material Notes:

Order this product through the following link:

http://www.lookpolymers.com/polymer_Cotronics-Resbond-908-High-Temperature-Ceramic-Adhesive-Moisture-Proof.php

Mechanical Properties	Metric	English	Comments
Flexural Strength	7.58 MPa	1100 psi	
Compressive Strength	20.7 MPa	3000 psi	

Thermal Properties	Metric	English	Comments
CTE, linear	8.10 $\mu\text{m}/\text{m}\cdot^\circ\text{C}$	4.50 $\mu\text{in}/\text{in}\cdot^\circ\text{F}$	
	@Temperature 20.0 $^\circ\text{C}$	@Temperature 68.0 $^\circ\text{F}$	
Thermal Conductivity	2.16 W/m-K	15.0 BTU-in/hr-ft ² - $^\circ\text{F}$	
Maximum Service Temperature, Air	1650 $^\circ\text{C}$	3000 $^\circ\text{F}$	

Electrical Properties	Metric	English	Comments
Volume Resistivity	1.00e+10 ohm-cm	1.00e+10 ohm-cm	
Dielectric Strength	7.87 kV/mm	200 kV/in	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China