

Covestro Baydur® 646 Polyurethane Structural Foam RIM, Density 15 pcf, MDI-based 2-Component Liquid System

Category : Other Engineering Material , Composite Core Material , Polymer , Thermoset , Polyurethane, TS , Thermoset Polyurethane Foam, Unreinforced

Material Notes:

0.25 in. thickness. RIM = Reaction Injection Molding Information provided by Bayer Corporation, Polyurethanes Division As of 1 September 2015, Bayer Material Science was separated from Bayer AG and officially adopted its new name – Covestro.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Covestro-Baydur-646-Polyurethane-Structural-Foam-RIM-Density-15-pcf-MDI-based-2-Component-Liquid-System.php

Physical Properties	Metric	English	Comments
Density	0.240 g/cc	0.00867 lb/in ³	ASTM D792
Apparent Bulk Density	0.240 g/cc	0.00867 lb/in ³	ASTM D792

Mechanical Properties	Metric	English	Comments
Hardness, Shore D	28	28	ASTM D2240
Tensile Strength, Ultimate	3.90 MPa	566 psi	ASTM D638/D412
Elongation at Break	7.0 %	7.0 %	ASTM D638/D412
Flexural Yield Strength	6.60 MPa	957 psi	ASTM D790
Flexural Modulus	0.220 GPa	31.9 ksi	ASTM D790
Compressive Yield Strength	3.00 MPa	435 psi	ASTM D395
Charpy Impact, Notched	0.380 J/cm ²	1.81 ft-lb/in ²	Bayer Test

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China