

Covestro Bayfit® Low Density Polyurethane Flexible Molded Foam,

Category : Polymer , Thermoset , Polyurethane, TS , Thermoset Polyurethane Foam, Unreinforced , Rubber or Thermoset Elastomer (TSE)

Material Notes:

Information provided by Bayer Corporation, Polyurethanes DivisionAs of 1 September 2015, Bayer MaterialScience was separated from Bayer AG and officially adopted its new name – Covestro.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Covestro-Bayfit-Low-Density-Polyurethane-Flexible-Molded-Foam.php

Physical Properties	Metric	English	Comments
Density	0.0270 g/cc	0.000975 lb/in ³	Core Density, ASTM D3574

Mechanical Properties	Metric	English	Comments
Tensile Strength, Ultimate	0.120 - 0.200 MPa	17.4 - 29.0 psi	ASTM D3574E
Elongation at Break	125 %	125 %	ASTM D3574E
Compression Set	12 - 22 %	12 - 22 %	Test D, ASTM D3574 Dry

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China